www.freeservicemanuals.info

JVC

SERVICE MANUAL

FLAT COLOR TELEVISION

AV-21VT14/P,
AV-21VT34/P

BASIC CHASSIS
CW



TABLE OF CONTENTS

1 PRECAUTION 1-3
2 SPECIFIC SERVICE INSTRUCTIONS 1-4
3 DISASSEMBLY 1-8
4 ADJUSTMENT 1-14
5 TROUBLESHOOTING 1-30

COPYRIGHT © 2004 Victor Company of Japan, Limited
Digitized in Heiloo Netherland

No.YA140
2004/10

SPECIFICATION

Items		Contents	
		AV-21VT14/P	AV-21VT34/P
Dimensions (W × H × D)		64.9cm × 46.55cm × 47.35cm	64.9cm × 47.8cm × 47.35cm
Mass		24kg	26.4kg
TV RF System		M	
Color System	TV Mode Video Mode	NTSC3.58 PAL / SECAM / NTSC3.58 / NTSC4.43	
Stereo System		MTS (Multi-Channel Television Sound)	
Receiving Frequency	VHF Low VHF High UHF CATV	46.25MHz ~ 168.25MHz (AU0 ~ S10) 175.25MHz ~ 463.25MHz (E5 ~ S41) 471.25MHz ~ 863.25MHz (E21 ~ CHINA 57) Mid : X ~ Z, S1 ~ S10 Super: S11 ~ S20 Hyper: S21 ~ S41	
Intermediate Frequency	VIF	38.0MHz	
	SIF	33.5MHz (4.5MHz)	
Color Sub Carrier Frequency		4.43MHz (PAL), 4.40MHz/4.25MHz (SECAM), 3.58MHz/4.43MHz (NTSC)	
Aerial Input Terminal		75Ω unbalanced, coaxial	
Power Input		AC110V-AC240V, 50Hz / 60Hz (Operating Voltage AC90V ~ AC260V)	
Power Consumption		121W (Max.) / 81W (Avg.)	143W (Max.) / 91W (Avg.)
Picture Tube ⚠		A51LVV896X 21-inch, aspect ratio 4:3, flat square face type, tinted	
Screen Size		Visible size :51.0cm (Diagonal) / 41.6cm × 31.5cm (H × V)	
High Voltage		29kV ± 1.5kV (at zero beam current)	
Speaker		6.5cm × 13cm, Oval type × 2	6.5cm × 13cm, oval type × 2 13cm, round type × 1 (Bass blaster unit)
Audio Output		7W + 7W	7W + 7W + 13W
Video / Audio Input [1/2/3]	S-Video [1]	Mini-DIN 4 pin × 1 Y: 1V(p-p), positive (negative sync provided), 75Ω C: 0.286V(p-p) (Burst signal), 75Ω	
	Video [1/2/3]	1V(p-p), negative sync, 75Ω, RCA pin jack × 3	
	Audio [1/2/3]	500mV(rms) (-4dBs), high impedance, RCA pin jack × 6	
	Component Video [2]	RCA pin jack × 3 Y:1V(p-p), positive (negative sync), 75Ω Cb/Cr:0.7V(p-p), 75Ω	
Video / Audio Output	Video Audio	1V(p-p), 75Ω, RCA pin jack × 1 500mV(rms)(-4dBs), Low impedance (400Hz when modulated 100%), RCA pin jack × 2	
Headphone		3.5mm stereo mini jack × 1	
Remote Control Unit		RM-C1282-2H (AA/R06/UM-3 battery × 2)	

Design & specifications are subject to change without notice.

Digitized in Heiloo Netherland

SECTION 1
PRECAUTION

1.1 SAFETY PRECAUTIONS

(1) The design of this product contains special hardware, many circuits and components specially for safety purposes. For continued protection, no changes should be made to the original design unless authorized in writing by the manufacturer. Replacement parts must be identical to those used in the original circuits. Service should be performed by qualified personnel only.

(2) Alterations of the design or circuitry of the products should not be made. Any design alterations or additions will void the manufacturer's warranty and will further relieve the manufacturer of responsibility for personal injury or property damage resulting therefrom.

(3) Many electrical and mechanical parts in the products have special safety-related characteristics. These characteristics are often not evident from visual inspection nor can the protection afforded by them necessarily be obtained by using replacement components rated for higher voltage, wattage, etc. Replacement parts which have these special safety characteristics are identified in the parts list of Service manual. **Electrical components having such features are identified by shading on the schematics and by (⚠) on the parts list in Service manual**. The use of a substitute replacement which does not have the same safety characteristics as the recommended replacement part shown in the parts list of Service manual may cause shock, fire, or other hazards.

(4) **Don't short between the LIVE side ground and ISOLATED (NEUTRAL) side ground or EARTH side ground when repairing.**
Some model's power circuit is partly different in the GND. The difference of the GND is shown by the LIVE : (⊥) side GND, the ISOLATED (NEUTRAL) : (⏚) side GND and EARTH : (⏚) side GND.
Don't short between the LIVE side GND and ISOLATED (NEUTRAL) side GND or EARTH side GND and never measure the LIVE side GND and ISOLATED (NEUTRAL) side GND or EARTH side GND at the same time with a measuring apparatus (oscilloscope etc.). If above note will not be kept, a fuse or any parts will be broken.

(5) If any repair has been made to the chassis, it is recommended that the B1 setting should be checked or adjusted (See B1 POWER SUPPLY check).

(6) The high voltage applied to the picture tube must conform with that specified in Service manual. Excessive high voltage can cause an increase in X-Ray emission, arcing and possible component damage, therefore operation under excessive high voltage conditions should be kept to a minimum, or should be prevented. If severe arcing occurs, remove the AC power immediately and determine the cause by visual inspection (incorrect installation, cracked or melted high voltage harness, poor soldering, etc.). To maintain the proper minimum level of soft X-Ray emission, components in the high voltage circuitry including the picture tube must be the exact replacements or alternatives approved by the manufacturer of the complete product.

(7) Do not check high voltage by drawing an arc. Use a high voltage meter or a high voltage probe with a VTVM. Discharge the picture tube before attempting meter connection, by connecting a clip lead to the ground frame and connecting the other end of the lead through a 10kΩ 2W resistor to the anode button.

(8) When service is required, observe the original lead dress. Extra precaution should be given to assure correct lead dress in the high voltage circuit area. Where a short circuit has occurred, those components that indicate evidence of overheating should be replaced. Always use the manufacturer's replacement components.

(9) **Isolation Check (Safety for Electrical Shock Hazard)**
After re-assembling the product, always perform an isolation check on the exposed metal parts of the cabinet (antenna terminals, video/audio input and output terminals, Control knobs, metal cabinet, screw heads, earphone jack, control shafts, etc.) to be sure the product is safe to operate without danger of electrical shock.

a) **Dielectric Strength Test**
The isolation between the AC primary circuit and all metal parts exposed to the user, particularly any exposed metal part having a return path to the chassis should withstand a voltage of 3000V AC (r.m.s.) for a period of one second. (. . . Withstand a voltage of 1100V AC (r.m.s.) to an appliance rated up to 120V, and 3000V AC (r.m.s.) to an appliance rated 200V or more, for a period of one second.)
This method of test requires a test equipment not generally found in the service trade.

b) **Leakage Current Check**
Plug the AC line cord directly into the AC outlet (do not use a line isolation transformer during this check.). Using a "Leakage Current Tester", measure the leakage current from each exposed metal part of the cabinet, particularly any exposed metal part having a return path to the chassis, to a known good earth ground (water pipe, etc.). Any leakage current must not exceed 0.5mA AC (r.m.s.).
However, in tropical area, this must not exceed 0.2mA AC (r.m.s.).

Alternate Check Method
Plug the AC line cord directly into the AC outlet (do not use a line isolation transformer during this check.). Use an AC voltmeter having 1000Ω per volt or more sensitivity in the following manner. Connect a 1500Ω 10W resistor paralleled by a 0.15μF AC-type capacitor between an exposed metal part and a known good earth ground (water pipe, etc.). Measure the AC voltage across the resistor with the AC voltmeter. Move the resistor connection to each exposed metal part, particularly any exposed metal part having a return path to the chassis, and measure the AC voltage across the resistor. Now, reverse the plug in the AC outlet and repeat each measurement. Any voltage measured must not exceed 0.75V AC (r.m.s.). This corresponds to 0.5mA AC (r.m.s.).
However, in tropical area, this must not exceed 0.3V AC (r.m.s.). This corresponds to 0.2mA AC (r.m.s.).



SECTION 2
SPECIFIC SERVICE INSTRUCTIONS

2.1 FEATURES

- New chassis design enables use of an interactive on-screen control.
- Pure flat CRT produces fine textured picture in every detail.
- Wide range voltage (110V ~ 240V) for AC power input.
- With AUDIO/VIDEO/S-VIDEO/COMPONENT input terminals.
- I^2C bus control utilizes single chip ICs.
- By means of AUTO PROGRAM, the TV stations can be selected automatically and the TV channels can also be rearranged automatically.
- Built-in DIGITAL ECO MODE (ECONOMY, ECOLOGY).
  In accordance with the brightness in a room, the brightness and/or contrast of the picture can be adjusted automatically to make the optimum picture which is easy on the eye.
- Built-in OFF TIMER & RETURN +.

2.2 MAIN DIFFERENCE LIST

⚠	Items	AV-21VT14/P	AV-21VT34/P
	BASS BLASTER	None	BASS BLASTER UNIT
	AUDIO OUTPUT	7W + 7W	7W + 7W + 13W
	POWER CONSUMPTION	121W (Max.) / 81W (Avg.)	143W (Max.) / 91W (Avg.)

Digitized in Heiloo Netherland

2.3 FUNCTIONS

■ REMOTE CONTROL UNIT

RM-C1282-2H



①	COLOR SYSTEM key
②	FAVORITE CHANNEL keys
③	DISPLAY BACK key
④	MENU (▲/▼, ◀/▶) keys
⑤	CLOSED CAPTION key
⑥	SOUND TURBO key
⑦	PICTURE MODE key
⑧	RETURN + key
⑨	OFF TIMER key
⑩	CHANNEL (-/+) keys
⑪	Not used
⑫	ECO key
⑬	POWER key
⑭	TV / VIDEO key
⑮	MENU (OK) key
⑯	MUTING key
⑰	Number keys
⑱	100+ key
⑲	VOLUME (-/+) keys
⑳	BASS key [AV-21VT34/P]
㉑	CINEMA SURROUND key

■ FRONT PANEL CONTROLS



①	HEADPHONE jack
②	IN (VIDEO-3) : VIDEO
③	IN (VIDEO-3) : AUDIO L/MONO
④	IN (VIDEO-3) : AUDIO R
⑤	MENU (OK) button
⑥	CHANNEL (-/+) buttons
⑦	VOLUME (-/+) buttons
⑧	Remote control sensor
⑨	ECO sensor
⑩	POWER lamp
⑪	MAIN POWER button

■ REAR TERMINAL

[AV-21VT14/P]



VIDEO-1 INPUT TERMINAL

1	S-VIDEO
2	VIDEO
3	AUDIO L/MONO
4	AUDIO R

COMPONENT (VIDEO-2) INPUT TERMINAL

5	Y/VIDEO
6	C_B
7	C_R
8	AUDIO L/MONO
9	AUDIO R

OUTPUT TERMINAL

10	VIDEO
11	AUDIO L
12	AUDIO R

13	Aerial input terminal

[AV-2VT34/P]



VIDEO-1 INPUT TERMINAL

1	S-VIDEO
2	VIDEO
3	AUDIO L/MONO
4	AUDIO R

COMPONENT (VIDEO-2) INPUT TERMINAL

5	Y/VIDEO
6	C_B
7	C_R
8	AUDIO L/MONO
9	AUDIO R

OUTPUT TERMINAL

10	VIDEO
11	AUDIO L
12	AUDIO R

BASS BLASTER UNIT OUTPUT TERMINAL

13	BASS SPEAKER OUT

14	Aerial input terminal

Digitized in Heiloo Netherland

2.4 MAIN CPU [MAIN PWB : IC701] PIN FUNCTION

Pin no.	Pin name	I/O	Remark
1	VssP2	-	GND
2	VssC4	-	GND
3	V1.8C4	I	1.8V (Digital)
4	V3.3A3	I	3.3V
5	VrefP_Sdac	I	3.3V (Positive)
6	VrefN_Sdac	-	GND
7	VrefP_Sdac	I	3.3V (Negative)
8	VrefN_Sdac	-	GND
9	VrefP_Sdac	I	3.3V (Positive)
10	XtalIn	I	24.567MHz for system clock
11	XtalOut	O	24.567MHz for system clock
12	VssA1	-	GND
13	NECK	I	V-guard input/ I/O switch
14	CONT	I	1.8V regulator control
15	V5P1	I	+5V
16	Ph2	-	Phase-2 filter
17	Ph1	-	Phase-1 filter
18	Gnd1	-	GND
19	SecPll	-	SECAM PLL decoupling
20	Dec8G	-	Bandgap decoupling
21	EW	O	East-West drive output
22	VDRB-	O	Vertical drive B output
23	VDRA+	O	Vertical drive A output
24	Vif1	I	Video IF input 1
25	Vif2	I	Video IF input 2
26	Vsc	-	Vertical sawtooth capacitor
27	Iref	I	Reference current input
28	GndIF	-	GND
29	Sif1	I	Sound IF input 1
30	Sif2	I	Sound IF input 2
31	AGC	O	Tuner AGC output
32	EHT	I	EHT/overvoltage protection input
33	Ssif/RefIn/Avl/RefOut	O	Automatic Volume Levelling/ sound IF input / subcarrier reference output / external reference signal input for I signal mixer for DVB operation
34	L3	I	Audio-L3 input (left signal)
35	R3	I	Audio-R3 input (right signal)
36	L_OUT	O	Audio L output
37	R_OUT	O	Audio R output
38	DecsDem	-	Decoupling sound demodulator
39	QssO/AmO/AudeEm	O	QSS intercarrier output / AM output / deemphasis / (front-end audio out)
40	Gnd2	-	GND
41	Pllif	-	IF-PLL loop filter
42	SifAgc	-	AGC sound IF
43	IfVo/FmRo/DvbO	O	Not used
44	NC	O	Not used
45	V8AudioSwitches	I	8V
46	AgcSsif	-	AGC capacitor second sound IF
47	V5P2	I	5V
48	V_OUT	O	Video output
49	L1	I	Audio-L1 input
50	R1	I	Audio-R1 input
51	V3	I	Video V3 input
52	C4	I	Not used
53	Audio2InL	I	Not used
54	Audio2InR	I	Not used
55	V2/Y	I	Video 2 input
56	L2	I	Audio L2 input (Left signal)
57	R2	I	Audio R2 input (right signal)
58	Y3/Cvbs	I	S-Video Y1 input
59	C1	I	S-Video C1 input
60	AudioLsL	O	Audio L output for audio power amplifier
61	AudioLsR	O	Audio R output for audio power amplifier
62	HP_L	O	Headphone L
63	HP_R	O	Headphone R

Pin no.	Pin name	I/O	Remark
64	CVBSO/PIP	O	CVBS / PIP output
65	SVM	O	Scan velocity modulation output
66	FbiSo	I	Flyback input/sandcastle output
67	Hout	O	Horizontal output
68	VssComb	-	GND
69	V5Comb	I	5V
70	Vin/R2/Pr	I	PIP R input
71	Uin/B2/Pb	I	PIP B input
72	Yin/G2/Y	I	PIP G input
73	Ysync	I	Not used
74	Yout	O	Not used
75	Uout/INSSW2	I	YUV insertion input
76	NC	O	Not used
77	INSSW3	I	YUV insertion input
78	R3/Pr	I	Component PR input (Video-2)
79	G3/Y	I	Component Y input (Video-2)
80	B3/Pb	I	Component PB input (Video-2)
81	Gnd3	-	GND
82	V5P3	I	5V
83	BCL	I	Beam current limiter input
84	BLKIN	I	Black current input
85	Rout	O	R output
86	Gout	O	G output
87	Bout	O	B output
88	V3.3A1	I	3.3V
89	RefAdN	-	GND
90	V3.3RefAdP	I	3.3V (Positive)
91	RefAd	I	3.3/2V
92	GndA	-	GND
93	V1.8A	I	1.8V
94	V3.3A2	I	3.3V
95	VssADC	-	GND
96	V1.8ADC	I	1.8V
97	REMOTE	I	Remote control
98	PW_LED	I	POWER LED control
99	P11/TO	I	POWER LED control
100	V1.8C2	I	1.8V
101	VssC2	-	GND
102	COMPONENT-PIP	-	Not used
103	COMB_SW_NT3.5/OTHER	-	Not used
104	VER_PROTECT	O	X-ray protect
105	S_REDUCE	O	Sound control
106	P00/I2SDI1	O	Not used
107	POWER	O	SUB POWER control
108	SCL1	I	I2C bus clock
109	SDA1	I/O	I2C bus clock
110	V3.3P	I	3.3V
111	ROTATION	O	ROTATION
112	3.58/OTHER	O	NTSC 3.58 detection
113	A_MUTE	O	Audio muting
114	4.5/OTHER	O	NTSC 4.43 detection
115	PROT	I	Protect
116	ECO_IN	I	ECO sensor level detection
117	V1.8C1	I	1.8V (Digital)
118	DecV1V8	I	1.8V
119	KEY_IN	I	Key scan data
120	VDO_DET	I	Video DET input
121	VSSC1+P1	-	Digital GND
122	P24/PWM3	I	S-Video DET input
123	P25/PWM4	O	GTVA_reset
124	V1.8C3	I	1.8V (Digital)
125	VssC3	-	GND
126	P12/Int2	I	External interrupt
127	SDA0	I/O	I2C bus data (for memory)
128	SCL0	I	I2C bus clock (for memory)

www.freeservicemanuals.info

SECTION 3
DISASSEMBLY

3.1 DISASSEMBLY PROCEDURE

3.1.1 REMOVING THE TWIN PORT BASS BLASTER UNIT [AV-21VT34/P]

- Unplug the power supply cord.
  (1) Disconnect the TWIN PORT BASS BLASTER UNIT's cord from the rear of the TV set.
  (2) Remove the TWIN PORT BASS BLASTER UNIT by pulling it upwards.

NOTE:

After removing the TWIN PORT BASS BLASTER UNIT, proceed to the following procedure.

3.1.2 REMOVING THE REAR COVER

- Unplug the power cord.
  (1) Remove the 9 screws **[A]** and 4 screws **[B]** as shown in Fig.1.
  (2) Withdraw the REAR COVER toward you.

CAUTION:

When reinstalling the rear cover, carefully push it inward after inserting the MAIN PWB into the REAR COVER groove.

3.1.3 REMOVING THE MAIN PW BOARD

- Remove the REAR COVER.
  (1) Slightly raise the both sides of the MAIN PWB by hand.
  (2) Withdraw the MAIN PWB backward.
  (If necessary, take off the wire clamp and connectors, etc.)

3.1.4 REMOVING THE SPEAKER

- Remove the REAR COVER.
  (1) Remove the 2 screws **[C]** as shown in Fig.1.
  (2) Follow the same steps when removing the other hand SPEAKER.

3.1.5 CHECKING THE MAIN PW BOARD

- To check the back side of the MAIN PWB.
  (1) Pull out the MAIN PWB. (Refer to REMOVING THE MAIN PW BOARD).
  (2) Erect the MAIN PWB vertically so that you can easily check its back side.

CAUTIONS:

- Before turning on power, make sure that the CRT earth wire and other connectors are properly connected.
- When repairing, connect the DEG. COIL to the DEG. connector on the MAIN PWB.
- When repairing, connect the DEG. COIL to the DEG. connector on the MAIN PWB.

3.1.6 WIRE CLAMPING AND CABLE TYING

(1) Be sure to clamp the wire.
(2) Never remove the cable tie used for tying the wires together.
Should it be inadvertently removed, be sure to tie the wires with a new cable tie.

Digitized in Heiloo Netherland


FRONT CABINET
PICTURE TUBE
C
(x2)
SPEAKER
MAIN PWB
(CRT SOCKET PWB)
FBT
MAIN PWB
C
(x2)
SPEAKER
BASS SPEAKER OUT JACK
[AV-21VT34/P]
TWIN PORT
BASS BLASTER UNIT
[AV-21VT34/P]
A
(x9)
REAR COVER
B
(x4)

Fig.1

3.2 REPLACEMENT OF MEMORY IC

3.2.1 MEMORY IC

This TV uses the following memory IC.

Memory IC: IC702 on MAIN PWB

The memory IC memorizes data for correctly operating the video and deflection circuits. When replacing the memory IC, be sure to use the same type IC written with the initial values of data. In other words, use the specific IC listed in "PRINTED WIRING BOARD PARTS LIST". For its mounting location, refer to "ADJUSTMENT LOCATIONS".

3.2.2 PROCEDURE FOR REPLACING MEMORY IC

1. Power off

Switch the power off and unplug the power cord from the wall outlet.

2. Replacing the memory IC

Replace the memory IC with new one. Be sure to use the memory IC written with the initial data values.

3. Power on

Plug the power cord into the wall outlet and switch the power on.

4. Check and setting of SYSTEM CONSTANT SET:

(1) Press the [DISPLAY] key and the [PICTURE MODE] key on the remote control unit simultaneously.
The SERVICE MENU screen will be displayed.(See Fig.1.)

(2) In the SERVICE MENU, press the [DISPLAY] key and [PICTURE MODE] key simultaneously. Then, the SYSTEM CONSTANT SET screen will be displayed.(See Fig.2.)

(3) Check whether the setting values of the SYSTEM CONSTANT SET are the same as those indicated in Table 1.
If the value is different, select the setting item with the MENU [▲] / [▼] key, and set the correct value with the MENU [◀] / [▶] key.

(4) Press the [DISPLAY] key twice to return to the normal screen.

5. Receive channel setting

Refer to the **OPERATING INSTRUCTIONS** and set the receive channels (channels preset).

6. User setting

Check the user setting values in Table 2 and Table 3. If setting value is different, set the correct value.
For setting, refer to the **OPERATING INSTRUCTIONS**.

7. Setting of SERVICE MENU

Verify the setting for each setting item in the SERVICE MENU.(See Table 4.) If readjustment is necessary, perform adjustment referring to "ADJUSTMENTS PROCEDURE".





Fig.1


SYSTEM CONSTANT-1
SYSTEM CONSTANT SET 1
SYSTEM OTHERS
COMB NO
TILT NO
SUPER BASS NO
▼ ▲ : SEL ◀ ▶ : OPE DISP : EXIT
SYSTEM CONSTANT-2
SYSTEM CONSTANT SET 2
SOUND STEREO
BLUE BACK MUTE NO
ECO SENSOR YES
▼ ▲ : SEL ◀ ▶ : OPE DISP : EXIT
SYSTEM CONSTANT-3
SYSTEM CONSTANT SET 3
SURROUND YES
PICTURE BOOSTER NO
COMPONENT YES
S INPUT YES
▼ ▲ : SEL ◀ ▶ : OPE DISP : EXIT

Fig.2

Digitized in Heiloo Netherland

3.2.3 FACTORY SETTING VALUE

■ **SETTING OF SYSTEM CONSTANT SET**

Setting item	Setting content	Setting value	
		AV-21VT14/P	AV-21VT34/P
SYSTEM	TAIWAN ↔ OTHERS	OTHERS	←
COMB	YES ↔ NO	NO	←
TILT	YES ↔ NO	NO	←
SUPER BASS	YES ↔ NO	NO	YES
SOUND	STEREO ↔ PB ↔ MONO	STEREO	←
BLUE BACK MUTE	YES ↔ NO	NO	←
ECO SENSOR	YES ↔ NO	YES	←
SURROUND	YES ↔ NO	YES	←
PICTURE BOOSTER	YES ↔ NO	NO	←
COMPONENT	YES ↔ NO	YES	←
S INPUT	YES ↔ NO	YES	←

Table 1

■ SETTING OF BASIC FUNCTIONS

Setting item	Setting value
POWER	Off
SUB POWER	On
VOLUME	15
COLOR SYSTEM	NTSC
SOUND SYSTEM	M
PICTURE MODE (VSM)	BRIGHT
CINEMA SURROUND	OFF
SUPER BASS	ON [AV-21VT34/P]
OFF TIMER	OFF
CLOSED CAPTION	OFF
CHANNEL POSITION	PR02

Table 2

■ SETTING OF MENU SCREEN

Setting item	Setting value
INPUT	TV
VNR	AUTO
COMPRESS (16:9)	OFF
AUTO SHUTOFF	OFF
CHILD LOCK	OFF
BLUE BACK	ON
VIDEO-2 SET	VIDEO
AUTO PROGRAM	Refer to OPERATING INSTRUCTIONS
CHANNEL SUMMARY	Refer to OPERATING INSTRUCTIONS
WHITE BALANCE	COOL
TINT	Center
COLOR	Center
BRIGHT	Center
PICTURE	Maximum
DETAIL	Center
BALANCE	Center
SOUND MODE	DYNAMIC
SOUND TURBO	OFF
AI VOLUME	ON
MTS	STEREO
FAVORITE CH RED	PR02
FAVORITE CH GREEN	PR03
FAVORITE CH YELLOW	PR04
FAVORITE CH BLUE	PR05
AI ECO SENSOR	OFF
AI ECO DISPLAY	ON

Table 3

■ SERVICE MENU SETTING ITEMS

Setting item	Setting value
1. IF	1. VCO 2. DELAY POINT
2. V/C	1. SCREEN 2. CUTOFF(B/G) 3. WDR(R/G/B) 4. BRIGHT(TV/VDO 1/2/3) 5. CONT(TV/VDO 1/2/3/TV 16:9/VDO 16:9) 6. COLOUR(TV/VDO1/2/3/DVD) 7. TINT(TV/VDO 1/2/3) 8. SHARP [Do not adjust] 9. Y DELAY [Do not adjust] 10. TINT DVD [Do not adjust] 11. AMP T. SHARP
3. AUDIO **[Do not adjust]**	1. DCXO ADJ 2. NICAM lower ERRLIM 3. NICAM upper ERRLIM 4. A2 ID THR 5. MENU EQUALIZER
4. DEF	1. V-SHIFT 2. V-SLOPE 3. V-SIZE 4. H-CENT 5. H-SIZE 6. TRAPEZ 7. EW-PIN 8. COR-UP 9. COR-LO 10. ANGLE 11. BOW 12. V-S.CR 13. V-LIN 14. V-ZOOM 15. V-SCROLL
5. VSM W/B **(BRIGHT/STANDARD/SOFT)** **(COOL/WARM/NORMAL)**	1. BRIGHT 2. CONT 3. COLOUR 4. SHARP 5. HUE 1. R DRIVE 2. G DRIVE 3. B DRIVE
6. STATUS **[Display only]**	
7. PLUG & PLAY(ON) **[Display only]**	

Table 4

Digitized in Heiloo Netherland

3.3 REPLACEMENT OF CHIP COMPONENT

3.3.1 CAUTIONS

(1) Avoid heating for more than 3 seconds.
(2) Do not rub the electrodes and the resist parts of the pattern.
(3) When removing a chip part, melt the solder adequately.
(4) Do not reuse a chip part after removing it.

3.3.2 SOLDERING IRON

(1) Use a high insulation soldering iron with a thin pointed end of it.
(2) A 30w soldering iron is recommended for easily removing parts.

3.3.3 REPLACEMENT STEPS

1. How to remove Chip parts

[Resistors, capacitors, etc.]

(1) As shown in the figure, push the part with tweezers and alternately melt the solder at each end.



(2) Shift with the tweezers and remove the chip part.



[Transistors, diodes, variable resistors, etc.]

(1) Apply extra solder to each lead.

(2) As shown in the figure, push the part with tweezers and alternately melt the solder at each lead. Shift and remove the chip part.



NOTE :
After removing the part, remove remaining solder from the pattern.

2. How to install Chip parts

[Resistors, capacitors, etc.]

(1) Apply solder to the pattern as indicated in the figure.



(2) Grasp the chip part with tweezers and place it on the solder. Then heat and melt the solder at both ends of the chip part.



[Transistors, diodes, variable resistors, etc.]

(1) Apply solder to the pattern as indicated in the figure.
(2) Grasp the chip part with tweezers and place it on the solder.
(3) First solder lead **A** as indicated in the figure.



(4) Then solder leads **B** and **C**.



SECTION 4
ADJUSTMENT

4.1 ADJUSTMENT PREPARATION

(1) **You can make the necessary adjustments for this unit with either the remote control unit or with the adjustment equipment and parts as given below.**
(2) **Adjustment with the remote control unit is made on the basis of the initial setting values, however, the new setting values used for setting the screen to its optimum condition may differ from the initial settings.**
(3) Make sure that AC power is turned on correctly.
(4) Turn on the power for the set and test equipment before use, and start the adjustment procedures after waiting at least 30 minutes.
(5) Unless otherwise specified, prepare the most suitable reception or input signal for adjustment.
(6) Never touch any adjustment parts, which are not specified in the list for this variable resistors, transformers, trimmer capacitors, etc.

4.2 PRESETTING BEFORE ADJUSTMENT

Unless otherwise specified in the adjustment instructions, preset the following functions with the remote control unit.

■ **User mode setting position**

Setting item	Setting value
PICTURE MODE (VSM)	BRIGHT
TINT, COLOR, BRIGHT,DETAIL	Center
PICTURE	Maximum
VNR	OFF
AI ECO SENSOR	OFF
BALANCE	Center
SOUND TURBO	OFF
CINEMA SURROUND	OFF
COMPRESS	4:3

4.3 MEASURING INSTRUMENT AND FIXTURES

(1) DC voltmeter (or Digital voltmeter)
(2) Oscilloscope
(3) Signal generator (Pattern generator) [PAL/SECAM/NTSC]
(4) Remote control unit

4.4 ADJUSTMENT ITEMS

■ B1 VOLTAGE
■ FOCUS ADJUSTMENT
■ IF CIRCUIT ADJUSTMENTS
• IF VCO adjustment
• DELAY POINT (AGC TAKE-OVER) adjustment
■ VIDEO CIRCUIT ADJUSTMENTS
• WHITE BALANCE (Low light) adjustment
• WHITE BALANCE (High light) adjustment
• SUB BRIGHT adjustment
• SUB CONTRAST adjustment
• SUB COLOR 1 adjustment
• SUB COLOR 2 adjustment
• SUB TINT 1 adjustment
• SUB TINT 2 adjustment
■ AUDIO SETTING
■ DEFLECTION CIRCUIT ADJUSTMENTS
• V.SLOPE adjustment
• V.POSITION adjustment
• V.HEIGHT adjustment
• H.POSITION adjustment
• V.LINEARITY adjustment
• H. PARALLEL adjustment
• H.BOW adjustment
■ VSM PRESET SETTING
■ PURITY AND CONVERGENCE ADJUSTMENTS
• PURITY adjustment
• STATIC CONVERGENCE adjustment
• DYNAMIC CONVERGENCE adjustment

Digitized in Heiloo Netherland

4.5 ADJUSTMENT LOCATIONS





4.6 BASIC OPERATION IN SERVICE MENU

Operate the SERVICE MENU with the remote control unit.

4.6.1 SERVICE MENU ITEMS

With the SERVICE MENU, various settings (adjustments) can be made, and they are broadly classified in the following items of settings:

1. IF	For entering/adjusting the setting values (adjustment values) of the IF circuit.
2. V/C	For entering/adjusting the setting values (adjustment values) of the VIDEO circuit.
3. AUDIO	For entering/adjusting the setting values (adjustment values) of the AUDIO circuit.
4. DEF	For entering/adjusting the setting values (adjustment values) of the DEFLECTION circuit.
5. VSM W/B	For setting the values of STANDARD, SOFT, BRIGHT and COOL, NORMAL, WARM.
6. STATUS	This is not used for service.
7. PLUG & PLAY (ON)	This is not used for service.

4.6.2 BASIC OPERATION IN SERVICE MENU

1. HOW TO ENTER SERVICE MENU

Press the [DISPLAY] key and the [PICTURE MODE] key on the remote control unit simultaneously.
The SERVICE MENU screen will be displayed. (See Fig. 1 on the next page.)

2. SELECTION OF SUB MENU SCREEN

Press one of the keys 1 to 6 on the remote control unit, and select the SUB MENU SCREEN from the SERVICE MENU. (See Fig.1 on the next page.)
SERVICE MENU → SUB MENU

1. IF
2. V/C
3. AUDIO
4. DEF
5. VSM W/B
6. STATUS
7. PLUG & PLAY (ON)

3. METHOD OF SETTING

NOTES:

- Once the setting values are set, they are memorized automatically.
- It must not be adjusted without inputting a signal.

(1) 1. IF

[1.VCO] : Under normal conditions, no adjustment is required.

(a) [1] key	Select **1. IF**.
(b) [1] key	Select **1. VCO**.
(c) [DISPLAY] key	When this is pressed twice, you will return to the SERVICE MENU.

[2.DELAY POINT]

(a) [1] key	Select **1. IF**.
(b) [2] key	Select **2. DELAY POINT**.
(c) MENU [◀] / [▶] key	Adjust the setting value.
(d) [DISPLAY] key	When this is pressed twice, you will return to the SERVICE MENU.

(2) 2. V/C, 3. AUDIO and 4. DEF

(a) [2] ~[4] keys	Select one from **2. V/C**, **3. AUDIO** and **4. DEF**
(b) MENU [▲] / [▼] key	Select setting items.
(c) MENU [◀] / [▶] key	Adjust the setting values of the setting items. Use the number keys on the remote control unit for setting the WHITE BALANCE. For the setting, refer to each item concerned.
(d) [DISPLAY] key	When this is pressed, you will return to the SERVICE MENU.

(3) 5. VSM W/B

(a) [5] keys	Select **5. VSM W/B**.
(b) MENU [OK] key	Select preset items.
(c) MENU [▲] / [▼] key	Adjust setting items.
(d) MENU [◀] / [▶] key	Adjust the setting values of the setting items.
(e) [DISPLAY] key	When this is pressed, you will return to the SERVICE MENU.

(4) 6. STATUS

This is for display only.

(5) 7. PLUG & PLAY (ON)

This is not used for service.

4. Release of SERVICE MENU

After completing the setting, return to the SERVICE MENU by pressing the [DISPLAY] key, then again press the [DISPLAY] key to return to the normal screen.

Digitized in Heiloo Netherland

4.6.3 SERVICE MENU FLOW CHART



Fig.1

4.7 ADJUSTMENT PROCEDURE

4.7.1 B1 VOLTAGE

Item	Measuring instrument	Test point	Adjustment part	Description
B1 VOLTAGE check	Signal generator DC voltmeter	B1 (pin 1) GND (pin 5) [CN00X connector in MAIN PWB]		(1) Receive a black and white signal. (2) Connect a DC voltmeter between B1 and GND (between pins 1 and 5 of the connector CN00X). (3) Make sure that the voltage is **DC134.5V ± 2V**.

4.7.2 FOCUS ADJUSTMENT

Item	Measuring instrument	Test point	Adjustment part	Description
FOCUS adjustment	Signal generator		FOCUS VR [In HVT]	**Notes:** • Set PICTURE MODE (VSM) to "BRIGHT". • The final adjustment of CONVERGENCE must be done after the FOCUS adjustment. (CONVERGENCE is affected by the FOCUS adjustment.) If any aeviation in CONVERGENCE is found, PURITY must be adjusted to restore the convergence. (1) Receive a crosshatch signal. (2) Adjust the **FOCUS VR** so that the vertical and horizontal lines will be clear and in fine detail on the screen. (3) Make sure that the picture is in focus even when the screen gets darkened.

4.7.3 IF CIRCUIT ADJUSTMENTS

Item	Measuring instrument	Test point	Adjustment part	Description
IF VCO check	Remote control unit		[1. IF] 1. VCO (CW)	**Note:** • Under normal conditions, no adjustment is required. (1) Receive a broadcast signal. (2) Select **1. IF** from the SERVICE MENU. (3) Select **1. VCO**. (4) Check the characters color of the **JUST REFERENCE** displayed to **yellow**. (5) Press the [DISPLAY] key three times to return to normal screen.



Item	Measuring instrument	Test point	Adjustment part	Description
DELAY POINT (AGC TAKE-OVER) adjustment	Remote control unit		[1. IF] 2. DELAY POINT	(1) Receive a black and white broadcast signal (color off). (2) Select **1. IF** from the SERVICE MENU. (3) Select **2. DELAY POINT**. (4) Adjust in order to eliminate any noise or beat from the image. Any increase above the initial value produces the noise and any decrease below it produces the beat. (5) Press the [DISPLAY] key three times to return to the normal screen. (6) Turn to other channels and make sure that there are no irregularities.

Adjustment item	Initial setting value	
	NTSC 3.58	
	VHF	UHF
2. DELAY POINT (AGC TAKE-OVER)	35	35

Digitized in Heiloo Netherland

4.7.4 VIDEO CIRCUIT ADJUSTMENTS

- The setting (adjustment) using the remote control unit is made on the basis of the initial setting values.
- The setting values which adjust the screen to the optimum condition can be different from the initial setting values.
- Do not change the initial setting values of the setting (adjustment) items not listed in "ADJUSTMENT PROCEDURE".
- The initial setting values in parenthesis ( ) are fixed offset values, needing no further adjustment.

Adjustment item		Variable range	Initial setting value					
			PAL	SECAM	NTSC3.58	NTSC4.43	COMPONENT (V-2)	
							525i	625i
1. SCREEN	BRI	0 ~ 63	32	32	32	32	32	32
2. CUTOFF	B	0 ~ 63 (-32 ~ +31)	11	11	11	11	(+3)	(+3)
	G	0 ~ 63 (-32 ~ +31)	7	7	7	7	(-5)	(-5)
3. WDR	R	0 ~ 63 (-32 ~ +31)	32	32	32	32	(0)	(0)
	G	0 ~ 63 (-32 ~ +31)	32	32	32	32	(0)	(0)
	B	0 ~ 63 (-32 ~ +31)	45	45	45	45	(0)	(0)
4. BRIGHT	RF	0 ~ 63 (-32 ~ +31)	---	---	39	---	---	---
	VIDEO 1(COMPOSITE/S)	(-32 ~ +31)	(+1)	(+1)	(+1)	(+1)	---	---
	VIDEO 2(COMPONENT)	(-32 ~ +31)	(+1)	(+1)	(+1)	(+1)	(+2)	(+2)
	VIDEO 3(COMPOSITE)	(-32 ~ +31)	(+1)	(+1)	(+1)	(+1)	---	---
5. CONT.	RF	0 ~ 63	---	---	32	---	---	---
	VIDEO	(-32 ~ +31)	(-3)	(-3)	(-3)	(-3)	(-2)	(-2)
	RF 16:9	(-32 ~ +31)	(-2)	(-2)	(-2)	(-2)	---	---
	VIDEO 16:9	(-32 ~ +31)	---	---	---	---	---	---
6. COLOUR	RF	0 ~ 63 (-32 ~ +31)	---	---	37	---	---	---
	VIDEO	0 ~ 63 (-32 ~ +31)	42	30	(+3)	(+3)	(+9)	(+0)
7. TINT	RF	0 ~ 63 (-32 ~ +31)	---	---	32	---	---	---
	VIDEO	(-32 ~ +31)	---	---	(+2)	(+2)	---	---
8. SHARP	RF	0 ~ 63	---	---	54	---	---	---
	VIDEO	0 ~ 63	54	54	54	54	40	40
9. Y DELAY	RF	0 ~ 15	---	---	3	---	---	---
	VIDEO	0 ~ 15	2	4	3	3	---	---
	S-VIDEO	0 ~ 15	7	10	7	7	---	---
10. TINT DVD	VIDEO, S-VIDEO	0 ~ 63	34	31	32	32	---	---
	COMPONENT	(-32 ~ +31)	---	---	---	---	(+1)	(0)
11. AMP T.SHARP	RF, VIDEO	0 ~ 63	0	0	0	0	0	0

Item	Measuring instrument	Test point	Adjustment part	Description
WHITE BALANCE (Low light) adjustment	Signal generator Remote control unit		[2. V/C] 2. CUTOFF (B) 2. CUTOFF (G) SCREEN VR [In HVT]	**Note:** • Set PICTURE MODE (VSM) to "BRIGHT". **- COMPOSITE WHITE BALANCE -** (1) Receive a PAL black and white signal (color off). (2) Select **2. V/C** from the SERVICE MENU. (3) Select **2. CUTOFF (B)** and **(G)**. (4) Set each value to initial setting value with the **[4]** / **[7]** keys and **[5]** / **[8]** keys. (5) Turn the **SCREEN VR** fully counterclockwise, then slowly turn it clockwise to where a red, blue or green color is faintly visible. (6) Use the **[4]** / **[7]** and **[5]** / **[8]** keys to adjust so that the other 2 colors appear white. (7) Turn the **SCREEN VR** to where the single horizontal line glows faintly. (8) Press the [DISPLAY] key twice to return to the normal screen. **- COMPONENT WHITE BALANCE -** (1) Receive a PAL component black and white signal (color off). (2) Select VIDEO-2 SET from the MENU and set VIDEO-2 SET to COMPONENT. (3) Adjust COMPONENT WHITE BALANCE in the same way as "COMPOSITE WHITE BALANCE".





Adjustment Item		Variable range	Initial setting value	
			COMPOSITE	COMPONENT
2. CUT OFF	B	0 ~ 63(-32~+31)	11	(+3)
	G	0 ~ 63(-32~+31)	7	(-5)

<table>
<tr><th>Item</th><th>Measuring instrument</th><th>Test point</th><th>Adjustment part</th><th>Description</th></tr>
<tr><td>WHITE BALANCE (High light) adjustment</td><td>Signal generator

Remote control unit</td><td></td><td>[2. V/C]
3. WDR (R)
3. WDR (G)
3. WDR (B)</td><td rowspan="2">Notes:
• Proceed to the following adjustment after having completed the WHITE BALANCE (Low light) adjustment.
• Set PICTURE MODE (VSM) to "BRIGHT".
(1) Receive a PAL black and white signal (color off).
(2) Select 2. V/C from the SERVICE MENU.
(3) Select 3. WDR (R), (G) and (B).
(4) Set each value to initial setting value with the [4] to [9] keys.
(5) Use the [4] to [9] keys to produce a white screen.
(6) Press the [DISPLAY] key twice to return to the normal screen.
<table><tr><th colspan="2">Adjustment Item</th><th>Variable range</th><th>Initial setting value</th></tr><tr><td rowspan="3">3. WDR</td><td>R</td><td>0 ~ 63</td><td>32</td></tr><tr><td>G</td><td>0 ~ 63</td><td>32</td></tr><tr><td>B</td><td>0 ~ 63</td><td>45</td></tr></table></td></tr>
<tr><td colspan="4"> 
</td></tr>
<tr><td>SUB BRIGHT adjustment</td><td>Remote control unit</td><td></td><td>[2. V/C]
4. BRIGHT</td><td>Notes:
• Proceed to the following adjustment after having completed the WHITE BALANCE (Low light) and WHITE BALANCE (High light) adjustment.
• Set PICTURE MODE (VSM) to "BRIGHT".
(1) Receive a broadcast.
(2) Select 2. V/C from the SERVICE MENU.
(3) Select 4. BRIGHT.
(4) Set the initial setting value.
(5) If the brightness is not best with the initial setting value, make fine adjustment until you get the best brightness.
(6) Press the [DISPLAY] key twice to return to the normal screen.</td></tr>
<tr><td>SUB CONTRAST adjustment</td><td>Remote control unit</td><td></td><td>[2. V/C]
5. CONT</td><td>Notes:
• Proceed to the following adjustment after having completed the SUB BRIGHT adjustment.
• Set PICTURE MODE (VSM) to "BRIGHT".
(1) Receive a broadcast.
(2) Select 2. V/C from the SERVICE MENU.
(3) Select 5. CONT.
(4) Set the initial setting value.
(5) If the contrast is not best with the initial setting value, make fine adjustment until you get the best contrast.
(6) Press the [DISPLAY] key twice to return to the normal screen.</td></tr>
</table>

Digitized in Heiloo Netherland

<table>
<tr><th>Item</th><th>Measuring instrument</th><th>Test point</th><th>Adjustment part</th><th>Description</th></tr>
<tr><td>SUB COLOR 1 adjustment</td><td>Remote control unit</td><td></td><td>[2. V/C]
6. COLOUR</td><td>[Method of adjustment without measuring instrument]
Notes:
• Proceed to the following adjustment after having completed the SUB CONTRAST adjustment.
• Set PICTURE MODE (VSM) to "BRIGHT".
- PAL COLOR -
(1) Receive a PAL broadcast.
(2) Select 2. V/C from the SERVICE MENU.
(3) Select 6. COLOUR.
(4) Set the initial setting value for PAL COLOR.
(5) If the color is not best with the initial setting value, adjust until you get the best color.
(6) Press the [DISPLAY] key twice to return to the normal screen.
- SECAM COLOR -
(1) Receive a SECAM broadcast.
(2) Press the [COLOR SYSTEM] key to select the SECAM color system.
(3) Adjust SECAM COLOR in the same way as for "PAL COLOR".
- NTSC 3.58 COLOR -
(1) Receive a NTSC 3.58MHz broadcast.
(2) Press the [COLOR SYSTEM] key to select the NTSC 3.58 color system.
(3) Adjust NTSC 3.58 COLOR in the same way as for "PAL COLOR".
- NTSC 4.43 COLOR -
When adjustment is done for NTSC 3.58 COLOR, appropriate values are automatically set for NTSC 4.43 COLOR.</td></tr>
<tr><td>SUB COLOR 2 adjustment</td><td>Signal generator

Oscilloscope

Remote control unit</td><td>TP-47G
TP-E
[CRT SOCKET PWB]</td><td>[2. V/C]
6. COLOUR</td><td rowspan="2">[Method of adjustment using measuring instrument]
Notes:
• Proceed to the following adjustment after having completed the SUB CONTRAST adjustment.
• Set PICTURE MODE (VSM) to "BRIGHT".
- PAL COLOR -
(1) Receive a PAL color bar signal (full field color bar 75% white).
(2) Select 2. V/C from the SERVICE MENU.
(3) Select 6. COLOUR.
(4) Set the initial setting value of PAL COLOR.
(5) Connect the oscilloscope between TP-47G and TP-E.
(6) Adjust PAL COLOR to set the value (A) in the figure to +12V.
- SECAM COLOR -
(1) Receive a SECAM color bar signal (color bar 75% white).
(2) Press the [COLOR SYSTEM] key to select the SECAM color system.
(3) Set the initial setting value of SECAM COLOR.
(4) Adjust SECAM COLOR to set the value (A) in the figure to ---.
- NTSC 3.58 COLOR -
(1) Receive a NTSC 3.58 color bar signal (full field color bar 75% white).
(2) Press the [COLOR SYSTEM] key to select the NTSC 3.58 color system.
(3) Set the initial setting value of NTSC 3.58 COLOR.
(4) Adjust NTSC 3.58 COLOR to set the value (A) in the figure to +4V.
- NTSC 4.43 COLOR -
When adjustment is done for NTSC 3.58 COLOR, appropriate values are automatically set for NTSC 4.43 COLOR.</td></tr>
<tr><td colspan="3"> 
</td></tr>
</table>

Item	Measuring instrument	Test point	Adjustment part	Description
SUB TINT 1 adjustment	Signal generator Remote control unit		[2. V/C] 7. TINT	**[Method of adjustment without measuring instrument]** **Notes:** • Proceed to the following adjustment after having completed the SUB CONTRAST adjustment. • Set PICTURE MODE (VSM) to "BRIGHT". **- NTSC 3.58 TINT -** (1) Receive a NTSC 3.58 color bar signal (full field color bar 75% white). (2) Press the [COLOR SYSTEM] key to select the NTSC 3.58 color system. (3) Select **2. V/C** from the SERVICE MENU. (4) Select **7. TINT**. (5) Set the initial setting value of NTSC 3.58. (6) If you cannot get the best tint with the initial setting value, make fine adjustment until you get the best tint. (7) Press the [DISPLAY] key twice to return to the normal screen. **- NTSC 4.43 TINT -** When adjustment is done for NTSC 3.58 TINT, appropriate values are automatically set for NTSC 4.43 TINT.
SUB TINT 2 adjustment	Signal generator Oscilloscope Remote control unit	TP-47G TP-E [CRT SOCKET PWB]	[2. V/C] 7. TINT	**[Method of adjustment using measuring instrument]** **Notes:** • Proceed to the following adjustment after having completed the SUB CONTRAST adjustment. • Set PICTURE MODE (VSM) to "BRIGHT". **- NTSC 3.58 TINT -** (1) Receive a NTSC 3.58 color bar signal (full field color bar 75% white). (2) Press the [COLOR SYSTEM] key to select the NTSC 3.58 color system. (3) Select **2. V/C** from the SERVICE MENU. (4) Select **7. TINT**. (5) Set the initial setting value of NTSC 3.58. (6) Connect the oscilloscope between TP-47G and TP-E. (7) Adjust NTSC 3.58 TINT to set the value **(B)** in the figure to **+4V**. (8) Press the [DISPLAY] key twice to return to the normal screen. **- NTSC 4.43 TINT -** When adjustment is done for NTSC 3.58 TINT, appropriate values are automatically set for NTSC 4.43 TINT.
				

4.7.5 AUDIO SETTING

This submenu is for display only, no adjustment is required.

[AV-21VT14/P]

Function	Item	100Hz	300Hz	1kHz	3kHz	8kHz
MENU EQUALIZER	DYNAMIC	+4	+3	-10	+3	+4
	MUSIC	+7	+2	+5	+2	+7
	NEWS	-6	+1	+6	+1	-6
	USER	0	0	0	0	0

[AV-21VT34/P]

Function	Item	100Hz	300Hz	1kHz	3kHz	8kHz
MENU EQUALIZER	DYNAMIC	+4	+3	0	+3	+4
	MUSIC	+1	+2	+6	+5	+6
	NEWS	-6	+1	+6	+1	-6
	USER	0	0	0	0	0

Digitized in Heiloo Netherland

4.7.6 DEFLECTION CIRCUIT ADJUSTMENTS

- The setting (adjustment) using the remote control unit is made on the basis of the initial setting values.
- The setting values which adjust the screen to the optimum condition can be different from the initial setting values.
- When performing deflection circuit adjustment, adjusts PAL signal (fv: 50 Hz) in 4:3 mode and 16:9 mode respectively, and adjust the NTSC signal (fv: 60 Hz) similarly.

Note:
Proceed to the following adjustment after having completed the adjustments of SUB BRIGHT and SUB PICTURE.

■ **4. DEF**

Adjustment item	Variable range		Initial setting value			
	4:3 50Hz	Others	4:3		COMPRESS (16:9)	
			50Hz	60Hz	50Hz	60Hz
1. V-SHIFT	0 ~ 63	-32 ~ +31	+32	0*	0*	0*
2. V-SLOPE	0 ~ 63	-32 ~ +31	+32	0*	0*	0*
3. V-SIZE	0 ~ 63	-32 ~ +31	+38	0*	-14	0
4. H-CENT	0 ~ 63	-32 ~ +31	+32	0*	0*	0*
5. H-SIZE	0 ~ 63	-32 ~ +31	0	0*	0*	0*
6. TRAPEZ	0 ~ 63	-32 ~ +31	0*	0*	0*	0*
7. EW-PIN	0 ~ 63	-32 ~ +31	0	0*	0*	0*
8. COR-UP	0 ~ 63	-32 ~ +31	0*	0*	0*	0*
9. COR-LO	0 ~ 63	-32 ~ +31	0*	0*	0*	0*
10. ANGLE	0 ~ 63	-32 ~ +31	+32	0*	0*	0*
11. BOW	0 ~ 63	-32 ~ +31	+32	0*	0*	0*
12. V-S.CR	0 ~ 63	-32 ~ +31	+32	0*	0*	0*
13. V-LIN	0 ~ 63	-32 ~ +31	+32	0*	0*	0*
14. V-ZOOM	0 ~ 63	-32 ~ +31	(+30)	0	-13	+3*
15. V-SCROLL	0 ~ 63	-32 ~ +31	(+32)	(0)	(0)	(0)

NOTE: The value with an asterisk * is variable for adjustment. The values in parenthesis ( ) are fixed values.

■ **COMPRESS: OFF (4:3)**

Item	Measuring instrument	Test point	Adjustment part	Description
V. SLOPE adjustment	Signal generator Remote control unit		[4. DEF] 2. V-SLOPE	**- PAL V. SLOPE -** (1) Receive a PAL circle pattern signal of vertical frequency 50Hz. (2) Select **4. DEF** from the SERVICE MENU. (3) Select **2. V-SLOPE**. (4) Set the initial setting value of **2. V-SLOPE**. (5) Adjust **2. V-SLOPE** to make "**A = B**". (6) Press the [DISPLAY] key twice to return to SERVICE MENU screen. **- NTSC V. SLOPE -** (1) Receive a NTSC circle pattern signal of vertical frequency 60Hz. (2) Make similar adjustment of NTSC V-SLOPE in the same way as for "PAL V-SLOPE".
				
V. POSITION adjustment	Signal generator Remote control unit		[4. DEF] 1. V-SHIFT	**- PAL V. POSITION -** (1) Receive a PAL circle pattern signal of vertical frequency 50Hz. (2) Select **1. V-SHIFT**. (3) Set the initial setting value of **1. V-SHIFT**. (4) Adjust **1. V-SHIFT** to make "**A = B**". **- NTSC V. POSITION -** (1) Receive a NTSC circle pattern signal of vertical frequency 60Hz. (2) Make similar adjustment of NTSC V. POSITION in the same way as for "PAL V. POSITION".
				

<table>
<tr><th>Item</th><th>Measuring instrument</th><th>Test point</th><th>Adjustment part</th><th>Description</th></tr>
<tr><td>V. HEIGHT adjustment</td><td>Signal generator

Remote control unit</td><td></td><td>[4. DEF]
3. V-SIZE
14. V-ZOOM</td><td rowspan="2">- PAL V. HEIGHT -
(1) Receive a PAL crosshatch signal.
(2) Select 3. V-SIZE.
(3) Set the initial setting value of 3. V-SIZE.
(4) Select 14. V-ZOOM.
(5) Set the initial setting value of 14. V-ZOOM.
(6) Adjust 14. V-ZOOM to make the vertical screen size to 92% of the picture size.
- NTSC V. HEIGHT -
(1) Receive a NTSC crosshatch signal.
(2) Make similar adjustment of NTSC V. HEIGHT in the same way as for "PAL V. HEIGHT".</td></tr>
<tr><td colspan="4"> 
</td></tr>
<tr><td>H. POSITION adjustment</td><td>Signal generator

Remote control unit</td><td></td><td>[4. DEF]
4. H-CENT</td><td rowspan="2">- PAL H. POSITION -
(1) Receive a PAL circle pattern signal.
(2) Select 4. H-CENT.
(3) Set the initial setting value of 4. H-CENT.
(4) Adjust 4. H-CENT to make "C = D".
- NTSC H. POSITION -
(1) Receive a NTSC circle pattern signal.
(2) Make similar adjustment of NTSC H. POSITION in the same way as for "PAL H. POSITION".</td></tr>
<tr><td colspan="4"> 
</td></tr>
<tr><td>V.LINEARITY adjustment</td><td>Signal generator

Remote control unit</td><td></td><td>[4. DEF]
12. V-S. CR
13. V-LIN</td><td rowspan="2">- PAL V. LINEARITY -
(1) Receive a PAL crosshatch signal.
(2) Select 12. V-S.CR.
(3) Set the initial setting value of 12. V-S. CR.
(4) Select 13. V-LIN.
(5) Set the initial setting value of 13. V-LIN.
(6) Adjust 12. V-S. CR and 13. V-LIN so that the spaces of each line on TOP, CENTER and BOTTOM become uniform.
- NTSC V. LINEARITY -
(1) Receive a NTSC crosshatch signal.
(2) Make similar adjustment of NTSC V-S. CR in the same way as for "PAL V-S. CR".</td></tr>
<tr><td colspan="4"> 
</td></tr>
</table>

Digitized in Heiloo Netherland

Item	Measuring instrument	Test point	Adjustment part	Description
H. PARALLEL adjustment	Signal generator Remote control unit		[4.DEF] 10. ANGLE	**- PAL H. PARALLEL -** (1) Receive a PAL crosshatch signal. (2) Select **10. ANGLE**. (3) Set the initial setting value of **10. ANGLE**. (4) Adjust **10. ANGLE** to optimize the trapezium distortion at the center of the screen. **- NTSC H. PARALLEL -** (1) Receive a NTSC crosshatch signal. (2) Make similar adjustment of NTSC H. PARALLEL in the same way as for "PAL H. PARALLEL".
				
H. BOW adjustment	Signal generator Remote control unit		[4.DEF] 11. BOW	**- PAL H. BOW -** (1) Receive a PAL crosshatch signal. (2) Select **11. BOW**. (3) Set the initial setting value of **11. BOW**. (4) Adjust **11. BOW** to optimize the horizontal arc distortion. **- NTSC H. BOW -** (1) Receive a NTSC crosshatch signal. (2) Make similar adjustment of NTSC H. BOW in the same way as for "PAL H. BOW". (3) Press the [DISPLAY] key twice to return to the normal screen.
				

■ **COMPRESS : ON (16:9)**

<table>
<tr><th>Item</th><th>Measuring instrument</th><th>Test point</th><th>Adjustment part</th><th>Description</th></tr>
<tr><td>V. HEIGHT adjustment</td><td>Signal generator

Remote control unit</td><td></td><td>[4.DEF]
14. V. ZOOM
3. V-SIZE</td><td rowspan="2">- PAL V. HEIGHT -
(1) Receive a PAL crosshatch signal of vertical frequency 50Hz.
(2) Press the [MENU] key and select PICTURE.
(3) Select PICTURE FEATURES.
(4) Select COMPRESS (16 : 9) and set COMPRESS to ON.
(5) Select 4. DEF from the SERVICE MENU.
(6) Set the initial setting value of 14. V. ZOOM.
(7) Select 3. V-SIZE.
(8) Set the initial setting value of 3. V-SIZE.
(9) Adjust 3. V-SIZE to set the vertical amplitude of the image to 305mm.

- NTSC V. HEIGHT -
(1) Receive a NTSC crosshatch signal of vertical frequency 60Hz.
(2) Make similar adjustment of NTSC V. HEIGHT in the same way as for "PAL V. HEIGHT".</td></tr>
<tr><td colspan="4"> 
</td></tr>
<tr><td>V. SLOPE adjustment</td><td>Signal generator

Remote control unit</td><td></td><td>[4.DEF]
2. V-SLOPE</td><td rowspan="2">- PAL V. SLOPE -
(1) Receive a PAL circle pattern signal of vertical frequency 50Hz.
(2) Select 4. DEF from the SERVICE MENU.
(3) Select 2. V-SLOPE.
(4) Set the initial setting value of 2. V-SLOPE.
(5) Adjust 2. V-SLOPE to make "A = B".
(6) Press the [DISPLAY] key to return to SERVICE MENU screen.

- NTSC V. SLOPE -
(1) Receive a NTSC circle pattern signal of vertical frequency 60Hz.
(2) Make similar adjustment of NTSC V-SLOPE in the same way as for "PAL V-SLOPE".</td></tr>
<tr><td colspan="4"> 
</td></tr>
</table>

Digitized in Heiloo Netherland

■ **VIDEO - 2 SET: COMPONENT**

Item	Measuring instrument	Test point	Adjustment part	Description
H. POSITION adjustment	Signal generator Remote control unit		[4. DEF] 4. H-CENT	(1) Receive a PAL circle pattern signal to VIDEO-2 component terminal. (2) Select VIDEO-2 SET from the MENU and set VIDEO-2 SET to COMPONENT. (3) Select **4. DEF** from the SERVICE MENU. (4) Select **4. H-CENT**. (5) Set the initial setting value of **4. H-CENT**. (6) Adjust **4. H-CENT** to make "**C=D**". (7) Press the [DISPLAY] key twice to return to the normal screen.



4.7.7 VSM PRESET SETTING

Item	Measuring instrument	Test point	Adjustment part	Description
VSM PRESET setting	Remote control unit		[5. VSM W/B] 1. BRIGHT 2. CONT 3.COLOUR 4. SHARP 5. HUE 1. R-DRIVE 2. G-DRIVE 3. B-DRIVE	(1) Select **5. VSM W/B** from the SERVICE MENU. (2) Select BRIGHT with the MENU [OK] key. (3) Set the value of **1. BRIGHT** ~ **5. HUE** to the values shown in the table. (4) Respectively select the VSM PRESET mode for SOFT and STANDARD. (5) Select COOL with the MENU [OK] key. (6) Set the values of **1. R-DRIVE** ~ **3. B-DRIVE** to the value shown in the table. (7) Select the W/B preset for WARM and NORMAL, respectively. (8) Press the [DISPLAY] key twice to return to the normal screen.

SUB MENU 5. VSM W/B



[Setting Values for SUB 5. VSM W/B]

VSM preset / Setting item	BRIGHT	STANDARD	SOFT
1. BRIGHT	0	+4	+4
2. CONT	+15	+4	+1
3. COLOUR	0	0	0
4. SHARP	0	0	-10
5. HUE	0	0	0
W/B preset / Setting item	**COOL**	**NORMAL**	**WARM**
1. R-DRIVE	0	0	+10
2. G-DRIVE	0	+2	-4
3. B-DRIVE	0	-10	-12

4.7.8 PURITY AND CONVERGENCE

■ **PURITY ADJUSTMENT**

Note:
The final adjustment of CONVERGENCE must be done after the FOCUS adjustment. (CONVERGENCE is changed by FOCUS adjustment.)
When makes difference by FOCUS adjustment, should be reconfirming PURITY adjustment.

(1) Demagnetize CRT with the demagnetizer.

(2) Loosen the retainer screw of the deflection yoke.

(3) Remove the wedges.

(4) Input a green raster signal from the signal generator, and turn the screen to green raster.

(5) Move the deflection yoke backward.

(6) Bring the long lug of the purity magnets on the short lug and position them horizontally. (Fig.2)

(7) Adjust the gap between two lugs so that the GREEN RASTER will come into the center of the screen. (Fig.3)

(8) Move the deflection yoke forward, and fix the position of the deflection yoke so that the whole screen will become green.

(9) Insert the wedge to the top side of the deflection yoke so that it will not move.

(10) Input a crosshatch signal.

(11) Verify that the screen is horizontal.

(12) Input red and blue raster signals, and make sure that purity is properly adjusted.



• P/C MAGNETS

P : PURITY MAGNET
4 : 4 POLES (convergence magnets)
6 : 6 POLES (convergence magnets)

Fig.1



Bring the long lug over the short lug and position them horizontally.

Fig.2



Fig.3

Digitized in Heiloo Netherland

■ STATIC CONVERGENCE ADJUSTMENT

(1) Input a crosshatch signal.

(2) Using 4-pole convergence magnets, overlap the red and blue lines in the center of the screen (Fig.1) and turn them to magenta (red/blue).

(3) Using 6-pole convergence magnets, overlap the magenta (red/blue) and green lines in the center of the screen and turn them to white.

(4) Repeat 2 and 3 above, and make best convergence.



Fig.1

■ DYNAMIC CONVERGENCE ADJUSTMENT

(1) Move the deflection yoke up and down and overlap the lines in the periphery. (Fig. 2)

(2) Move the deflection yoke left to right and overlap the lines in the periphery. (Fig. 3)

(3) Repeat 1 and 2 above, and make best convergence.

(4) Adjust XV by XV coil. (Fig.4)



Fig.2

- After adjustment, fix the wedge at the original position. Fasten the retainer screw of the deflection yoke. Fix the P/C magnets with glue.



Fig.3



Fig.4

SECTION 5
TROUBLESHOOTING

5.1 SELF CHECK FUNCTIONS

5.1.1 OUTLINE

This model has self check functions given below. When an abnormality has been detected, the SUB POWER is turned off and POWER LED flashes to inform of the failure. An abnormality is detected by the signal input state of the control line connected to the microcomputer.

5.1.2 SELF CHECK ITEMS

Check item	Details of detection	Method of detection	State of abnormality
B1 over-current protection	An over-current on the low B1 line is detected.	The main microcomputer detects the possible abnormality at 24-msec. intervals and judges the results in every 16 time. Of the 16 times, if NG is detected more than 9 times, it is judged that there is an abnormality.	When an abnormality has been detected, the SUB-POWER is turned off. While the SUB-POWER is being turned off, the POWER key on the remote control unit is not operational until the power cord is disconnected and connected again.
CRT neck broken protection	Operation of CRT neck protection circuit.		

5.1.3 SELF CHECK INDICATING FUNCTION

When an abnormality has been detected at about 5 seconds after the power was turned on, the SUB POWER is turned off immediately and the POWER LED flashes.



[INDICATION BY THE POWER LED]

Item	LED flashing intervals
B1 over-current protection / CRT neck broken protection	0.3 seconds

Digitized in Heiloo Netherland

www.freeservicemanuals.info 7/23/2017

JVC
Victor Company of Japan, Limited
AV & MULTIMEDIA COMPANY VIDEO DISPLAY CATEGORY 12, 3-chome, Moriya-cho, kanagawa-ku, Yokohama, kanagawa-prefecture, 221-8528, Japan

(No.YA140)

Digitized in Heiloo Netherland

Printed in Japan
VPT

PARTS LIST

CAUTION

- The parts identified by the ⚠ symbol are important for the safety . Whenever replacing these parts, be sure to use specified ones to secure the safety.
- The parts not indicated in this Parts List and those which are filled with lines --- in the Parts No. columns will not be supplied.
- P.W. BOARD Ass'y will not be supplied, but those which are filled with the Parts No. in the Parts No. columns will be supplied.

ABBREVIATIONS OF RESISTORS, CAPACITORS AND TOLERANCES

RESISTORS		CAPACITORS	
CR	Carbon Resistor	C CAP.	Ceramic Capacitor
FR	Fusible Resistor	E CAP.	Electrolytic Capacitor
PR	Plate Resistor	M CAP.	Mylar Capacitor
VR	Variable Resistor	CH CAP.	Chip Capacitor
HV R	High Voltage Resistor	HV CAP.	High Voltage Capacitor
MF R	Metal Film Resistor	MF CAP.	Metalized Film Capacitor
MG R	Metal Glazed Resistor	MM CAP.	Metalized Mylar Capacitor
MP R	Metal Plate Resistor	MP CAP.	Metalized Polystyrol Capacitor
OM R	Metal Oxide Film Resistor	PP CAP.	Polypropylene Capacitor
CMF R	Coating Metal Film Resistor	PS CAP.	Polystyrol Capacitor
UNF R	Non-Flammable Resistor	TF CAP.	Thin Film Capacitor
CH V R	Chip Variable Resistor	MPP CAP.	Metalized Polypropylene Capacitor
CH MG R	Chip Metal Glazed Resistor	TAN. CAP.	Tantalum Capacitor
COMP. R	Composition Resistor	CH C CAP.	Chip Ceramic Capacitor
LPTC R	Linear Positive Temperature Coefficient Resistor	BP E CAP.	Bi-Polar Electrolytic Capacitor
		CH AL E CAP.	Chip Aluminum Electrolytic Capacitor
		CH AL BP CAP.	Chip Aluminum Bi-Polar Capacitor
		CH TAN. E CAP.	Chip Tantalum Electrolytic Capacitor
		CH AL BP E CAP.	Chip Tantalum Bi-Polar Electrolytic Capacitor

RESISTORS									
F	G	J	K	M	N	R	H	Z	P
±1%	±2%	±5%	±10%	±20%	±30%	+30% -10%	+50% -10%	+80% -20%	+100% -0%

Digitized in Heiloo Netherland

CONTENTS

USING P.W. BOARD & REMOTE CONTROL UNIT 3-3
EXPLODED VIEW PARTS LIST -1 3-3
EXPLODED VIEW -1 3-3
EXPLODED VIEW PARTS LIST -2 3-4
EXPLODED VIEW -2 3-5
EXPLODED VIEW PARTS LIST -3 [AV-21VT34/P] 3-6
EXPLODED VIEW -3 3-6

PRINTED WIRING BOARD PARTS LIST [AV-21VT14/P] 3-7
MAIN P.W. BOARD ASS'Y (SCW-1039A-H2) 3-7

PRINTED WIRING BOARD PARTS LIST [AV-21VT34/P] 3-11
MAIN P.W. BOARD ASS'Y (SCW-1038A-H2) 3-11

REMOTE CONTROL UNIT PARTS LIST (RM-C1282-2H) 3-15
PACKING 3-15
PACKING PARTS LIST 3-15

Digitized in Heiloo Netherland

USING P.W. BOARD & REMOTE CONTROL UNIT

P.W.B ASS'Y	AV-21VT14/P	AV-21VT34/P
MAIN P.W.B	SCW-1039A-H2	SCW-1038A-H2
REMOTE CONTROL UNIT	RM-C1282-2H	←

EXPLODED VIEW PARTS LIST -1

⚠	Ref.No.	Part No.	Part Name	Description	Local
	1	GG30068-001A-H	AV SHEET		
	2	GG40023-003A-H	JVC MARK		
	3	GG30044-001B-H	REMOCON LENS		
	4	GG30042-001B-H	LED LENS		
⚠	100	GG10238-008A-H	FRONT CABINET ASS'Y	Inc.101,102,103,104	
	101	GG20044-004A-H	DOOR		
	102	GG30043-002A-H	POWER KNOB		
	103	CM35235-003-H	SPRING		
	104	GG20022-002B-H	CONTROL KNOB		

EXPLODED VIEW -1



EXPLODED VIEW PARTS LIST -2

⚠	Ref.No.	Part No.	Part Name	Description	Local
⚠	V01	A51LVV896X	CRT		
⚠	DY01	QQD0082-001	DEF YOKE		
⚠	L01	QQW0146-001	DEG COIL		
⚠	T522	QQH0188-001	FB TRANSF		
	11	QYSBSBG4016ZA	TAP SCREW	M4 x 16mm(x9)	
	12	QYSBSF3010ZA	TAP SCREW	M3 x 10mm(x4)	
⚠	13	GG10187-007A-H	REAR COVER		AV-21VT14/P
⚠	13	GG10187-008A-H	REAR COVER		AV-21VT34/P
⚠	14	CM47005-A01-H	POWER CORD CLAMP		
⚠	15	QMPR380-165-K2	POWER CORD	1.65m BLACK	
	16	QAL0608-001	PC MAGNET		
	17	CE40764-00A	WEDGE ASS'Y	(x3)	
	18	A48457-3-H	SPRING		
	19	CHGB0028-0A	BRAIDED ASS'Y		
	20	CHGB0017-0C	BRAIDED SUB ASS'Y		
	21	CM36623-B01-H	CHASSIS RAIL	(x2)	
	22	GG40046-001A-H	TAPPING SCREW	(x4)	
	23	LC40226-004A-H	SPACER	(x4)	
	24	GG20057-001A-H	SP HOLDER	(x4)	
	25	QAS0139-001	SPEAKER	(x2) SP01,SP02	
⚠	26	GG20024-001B-H	RATING LABEL		
⚠	30	SCW-1039A-H2	MAIN PWB		AV-21VT14/P
⚠	30	SCW-1038A-H2	MAIN PWB		AV-21VT34/P

Digitized in Heiloo Netherland

EXPLODED VIEW -2



EXPLODED VIEW PARTS LIST -3 [AV-21VT34/P]

⚠	Ref.No.	Part No.	Part Name	Description	Local
	50	LC40352-001A-H	RUBBER SHEET	(x4)	
	51	QYSBSFG4016ZA	TAP SCREW	M4 x 16mm(x13)	
	52	GG10141-001C-H	BASS BOTTOM		
	53	LC41211-001A	SOUND ABSORBER		
	54	QYSBSFG4016ZA	TAP SCREW	M4 x 16mm(x4)	
	55	QAS0118-001	SPEAKER	SP03	
	56	WJJ0266-002A	E-SIC WIRE C-C		
	57	GG30022-001A-H	BASS DUCT R	(x2)	
	58	GG10140-001C-H	BASS TOP		

EXPLODED VIEW -3



Digitized in Heiloo Netherland

www.freeservicemanuals.info

PRINTED WIRING BOARD PARTS LIST [AV-21VT14/P]

MAIN P.W. BOARD ASS'Y (SCW-1039A-H2)

⚠Ref No.	Part No.	Part Name	Description	Local
IC302	S9066-11	PHOTO CONDUCTOR		
IC351	TDA6107AJF/N1	IC		
IC401	AN15525A	IC		
IC601	AN5277	IC		
IC701	TDA12027-NTSC	IC(MCU)	(SERVICE)	
IC702	AT24C16-21VT34P	IC	(SERVICE)	
IC801	RPM7238-H5	IR DETECT UNIT		
IC921	STR-W6756-F5	SW IC		
IC951	SE135N	IC		
IC972	BA33BC0T	REGULATOR IC		
IC973	PQ120RDA1SZ	IC		
IC974	MM1561JF-X	IC		
IC975	PQ050RDA1SZ	IC		
IC976	MM1561JF-X	IC		
Q001	2SK1374-X	MOS FET		
Q002	2SK1374-X	MOS FET		
Q101	2SC5083/L-P/-T	TRANSISTOR		
Q341	2SA1530A/QR/-X	TRANSISTOR		
Q521	2SC2655/Y/-T	TRANSISTOR		
⚠Q522	TT2190LS-YB11	TRANSISTOR		
Q571	2SA1208/ST/Z1-T	TRANSISTOR		
Q572	UN2212-X	DIGI TRANSISTOR		
Q601	2SA1530A/QR/-X	TRANSISTOR		
Q602	2SA1530A/QR/-X	TRANSISTOR		
Q603	DTC323TK-X	DIGI TRANSISTOR		
Q605	DTC323TK-X	DIGI TRANSISTOR		
Q607	2SC3928A/QR/-X	TRANSISTOR		
Q608	2SC3928A/QR/-X	TRANSISTOR		
Q609	UN2212-X	DIGI TRANSISTOR		
Q611	UN2212-X	DIGI TRANSISTOR		
Q703	2SA1530A/QR/-X	TRANSISTOR		
Q704	2SC3928A/QR/-X	TRANSISTOR		
Q705	SSM3K02F-X	MOS FET		
Q706	SSM3K02F-X	MOS FET		
Q707	2SC3928A/QR/-X	TRANSISTOR		
Q708	2SA1530A/QR/-X	TRANSISTOR		
Q791	DTC124ESA-T	DIGI TRANSISTOR		
Q801	KTA1267/YG/-T	TRANSISTOR		
Q803	DTC323TK-X	DIGI TRANSISTOR		
Q804	DTC323TK-X	DIGI TRANSISTOR		
Q805	2SA1530A/QR/-X	TRANSISTOR		
Q955	2SC3928A/QR/-X	TRANSISTOR		
D341	MA8033/H/-X	Z DIODE		
D342	MA8033/H/-X	Z DIODE		
D343	MA8033/H/-X	Z DIODE		
D345	MA111-X	SI DIODE		
D349	MA8120/M/-X	Z DIODE		
D350	MA8075/M/-X	Z DIODE		
D351	EU01N-T2	SI DIODE		
D354	RGP10J-5025-T3	SI DIODE		
D355	RGP10J-5025-T3	SI DIODE		
D356	RGP10J-5025-T3	SI DIODE		
D422	MTZJ75-T2	Z DIODE		
D423	1N4003-T2	SI DIODE		
D471	1SR124-400A-T2	SI DIODE		
D472	MA111-X	SI DIODE		
D520	MA111-X	SI DIODE		
D521	ERB06-15-F1	SI DIODE		
D522	RU3AM-LFC4	SI DIODE		
D523	RGP10J-5025-T3	SI DIODE		
D530	RGP10J-5025-T3	SI DIODE		
D551	RGP10J-5025-T3	SI DIODE		
D552	RGP10J-5025-T3	SI DIODE		
D554	MA8051/L/-X	Z DIODE		
D571	MA8075/H/-X	Z DIODE		
D581	RGP10J-5025-T3	SI DIODE		
D601	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J	
D603	MA111-X	SI DIODE		
D604	MA8300/H/-X	Z DIODE		
D605	MA8300/H/-X	Z DIODE		
D607	1SS133-T2	SI DIODE		
D701	MA111-X	SI DIODE		
D702	MA8091/H/-X	Z DIODE		
D704	MA8091/H/-X	Z DIODE		
D706	MA8036-X	Z DIODE		
D707	MA111-X	SI DIODE		
D708	MA111-X	SI DIODE		
D709	MA111-X	SI DIODE		
D710	MA8091/H/-X	Z DIODE		
D711	MA8051/M/-X	Z DIODE		
D712	MA8051/M/-X	Z DIODE		
D713	MA8039/H/-X	Z DIODE		
D714	MA8030/H/-X	Z DIODE		
D751	MA8091/H/-X	Z DIODE		
D753	MA8091/H/-X	Z DIODE		
D791	MA8062/M/-X	Z DIODE		
D801	NCB31HK-152X	C CAPACITOR	1500pF 50V K	
D802	NCB31HK-152X	C CAPACITOR	1500pF 50V K	
D803	NCB31HK-152X	C CAPACITOR	1500pF 50V K	
D804	NCB31HK-152X	C CAPACITOR	1500pF 50V K	
D808	LH22440-T16	LED	POWER(RED)	
D810	MA8091/H/-X	Z DIODE		
D811	MA8091/H/-X	Z DIODE		
D812	MA8091/H/-X	Z DIODE		
D813	MA8091/H/-X	Z DIODE		
D814	MA8091/H/-X	Z DIODE		
D815	NCB31HK-152X	C CAPACITOR	1500pF 50V K	
D816	NCB31HK-152X	C CAPACITOR	1500pF 50V K	
D817	MA8091/H/-X	Z DIODE		
D901	GSIB460	BRIDGE DIODE		
D921	RGP10J-5025-T3	SI DIODE		
D922	1SS133-T2	SI DIODE		
D926	RGP10M-5010-T3	SI DIODE		
D927	1SS133-T2	SI DIODE		
D928	MA8240/M/-X	Z DIODE		
D929	MA111-X	SI DIODE		
D931	MA8062/M/-X	Z DIODE		
D932	MTZJ27B-T2	Z DIODE		
D933	MTZJ9.1C-T2	Z DIODE		
D934	MTZJ9.1C-T2	Z DIODE		
D935	MTZJ9.1C-T2	Z DIODE		
D951	31DF6N-FC5	SI DIODE		
D952	FSF05A20	SI DIODE		
D953	RGP10J-5025-T3	SI DIODE		
D955	FSF05A20	SI DIODE		
D956	MA111-X	SI DIODE		
D957	MA111-X	SI DIODE		
D962	MA8330/M/-X	Z DIODE		
D970	MA8082/M/-X	Z DIODE		
D971	MA111-X	SI DIODE		
D973	MA111-X	SI DIODE		
D975	MA111-X	SI DIODE		
D977	MA111-X	SI DIODE		
D980	QQR1114-001Z	FERRITE BEADS		
C001	NCB31HK-103X	C CAPACITOR	0.01uF 50V K	
C002	QETN1HM-106Z	E CAPACITOR	10uF 50V M	
C003	NCB31HK-104X	C CAPACITOR	0.1uF 50V K	
C004	QETN1CM-477Z	E CAPACITOR	470uF 16V M	
C005	NCB31HK-222X	C CAPACITOR	2200pF 50V K	
C006	QETN1CM-336Z	E CAPACITOR	33uF 16V M	
C101	NCB31HK-103X	C CAPACITOR	0.01uF 50V K	
C102	NCB31HK-103X	C CAPACITOR	0.01uF 50V K	
C103	NCB31HK-103X	C CAPACITOR	0.01uF 50V K	
C104	QETN1EM-476Z	E CAPACITOR	47uF 25V M	
C106	NCB31HK-103X	C CAPACITOR	0.01uF 50V K	
C109	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J	
C110	NCB31HK-104X	C CAPACITOR	0.1uF 50V K	
C111	QETN1CM-477Z	E CAPACITOR	470uF 16V M	
C317	QETN1HM-105Z	E CAPACITOR	1uF 50V M	
C341	QETN1CM-107Z	E CAPACITOR	100uF 16V M	
C351	NDC31HJ-102X	C CAPACITOR	1000pF 50V J	
C352	QETN2EM-475Z	E CAPACITOR	4.7uF 250V M	
C353	QFKC2EK-104Z	MM CAPACITOR	0.1uF 250V K	
C358	QCZ0364-152	C CAPACITOR	1500pF 2kV K	
C422	QCS32HJ-180Z	C CAPACITOR	18pF 500V J	
C423	NCB31HK-682X	C CAPACITOR	6800pF 50V K	
C424	QFLC2AJ-683Z	M CAPACITOR	0.068uF 100V J	
C427	QETM1VM-108	E CAPACITOR	1000uF 35V M	
C428	QEHR1VM-227Z	E CAPACITOR	220uF 35V M	
C430	QFLC2AJ-563Z	M CAPACITOR	0.056uF 100V J	
C431	QFVF1HJ-184Z	MF CAPACITOR	0.18uF 50V J	
C435	NCF21HZ-334X	C CAPACITOR	0.33uF 50V Z	
C436	NCF21HZ-334X	C CAPACITOR	0.33uF 50V Z	
C471	QETN1HM-106Z	E CAPACITOR	10uF 50V M	
C520	NCB31HK-104X	C CAPACITOR	0.1uF 50V K	
C521	QCB31HK-332Z	C CAPACITOR	3300pF 50V K	
C522	QFLC1HJ-223Z	M CAPACITOR	0.022uF 50V J	
C523	QETN1VM-476Z	E CAPACITOR	47uF 35V M	
⚠C524	QFZ0196-202	MPP CAPACITOR	2000pF 1.5kV H	
C525	QFZ0196-502	MPP CAPACITOR	5000pF 1.5kV H	
C526	QFZ0196-202	MPP CAPACITOR	2000pF 1.5kV H	
C527	QFZ0197-124	MPP CAPACITOR	0.12uF 250V J	
C528	QFP32GJ-393	PP CAPACITOR	0.039uF 400V J	

Digitized in Heiloo Netherland

⚠Ref No.	Part No.	Part Name	Description Local
C529	QETN2EM-475Z	E CAPACITOR	4.7uF 250V M
C530	QCB32HK-561Z	C CAPACITOR	560pF 500V K
C532	QETN2EM-106Z	E CAPACITOR	10uF 250V M
C551	QCB32HK-561Z	C CAPACITOR	560pF 500V K
C552	QCB32HK-561Z	C CAPACITOR	560pF 500V K
C553	QEHR1EM-108Z	E CAPACITOR	1000uF 25V M
C554	QEHR1EM-108Z	E CAPACITOR	1000uF 25V M
C555	QFLC2AJ-103Z	M CAPACITOR	0.01uF 100V J
C571	QEZ0203-107	E CAPACITOR	100uF 160V M
C572	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C573	QETN1EM-476Z	E CAPACITOR	47uF 25V M
C581	QFVF1HJ-104Z	MF CAPACITOR	0.1uF 50V J
C582	QFZ0197-124	MPP CAPACITOR	0.12uF 250V J
C601	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C602	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C603	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C604	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C605	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C606	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C607	QETN1CM-227Z	E CAPACITOR	220uF 16V M
C608	QETN1CM-227Z	E CAPACITOR	220uF 16V M
C609	QETN1HM-336Z	E CAPACITOR	33uF 50V M
C610	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C613	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C615	QETM1VM-108	E CAPACITOR	1000uF 35V M
C616	QETM1VM-108	E CAPACITOR	1000uF 35V M
C656	QETN1HM-107Z	E CAPACITOR	100uF 50V M
C661	QETN1CM-227Z	E CAPACITOR	220uF 16V M
C662	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C701	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C702	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C703	QETN1CM-477Z	E CAPACITOR	470uF 16V M
C704	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C705	NDC31HJ-3R0X	C CAPACITOR	3pF 50V J
C706	NDC31HJ-3R0X	C CAPACITOR	3pF 50V J
C707	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C708	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C709	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C710	NCB31HK-682X	C CAPACITOR	6800pF 50V K
C711	QETN1HM-225Z	E CAPACITOR	2.2uF 50V M
C712	QFVF1HJ-224Z	MF CAPACITOR	0.22uF 50V J
C713	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C714	NCB31HK-223X	C CAPACITOR	0.022uF 50V K
C715	NCB31HK-102X	C CAPACITOR	1000pF 50V K
C716	NCB31HK-102X	C CAPACITOR	1000pF 50V K
C717	NCB31HK-473X	C CAPACITOR	0.047uF 50V K
C718	QFVF1HJ-104Z	MF CAPACITOR	0.1uF 50V J
C719	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C720	NCB31HK-102X	C CAPACITOR	1000pF 50V K
C723	NCB21CK-105X	C CAPACITOR	1uF 16V K
C724	NCB21CK-105X	C CAPACITOR	1uF 16V K
C726	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C727	NCB31HK-332X	C CAPACITOR	3300pF 50V K
C728	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C729	QETN1HM-225Z	E CAPACITOR	2.2uF 50V M
C730	QETN1HM-226Z	E CAPACITOR	22uF 50V M
C731	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C732	QETN1HM-225Z	E CAPACITOR	2.2uF 50V M
C733	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C734	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C735	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C736	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C737	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C738	NCB21CK-105X	C CAPACITOR	1uF 16V K
C739	NCB21CK-105X	C CAPACITOR	1uF 16V K
C740	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C741	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C742	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C743	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C744	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C745	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C746	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C747	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C748	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C749	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C750	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C751	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C752	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C753	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C754	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C755	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C756	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C757	NDC31HJ-561X	C CAPACITOR	560pF 50V J
C758	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C759	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C760	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C761	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C762	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C763	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C764	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C765	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C766	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C767	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C768	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C770	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C771	QETN1HM-226Z	E CAPACITOR	22uF 50V M
C772	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C773	QETN1HM-225Z	E CAPACITOR	2.2uF 50V M
C774	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C775	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C776	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C777	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C778	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C779	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C780	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C781	NCB21CK-105X	C CAPACITOR	1uF 16V K
C782	NCB21CK-105X	C CAPACITOR	1uF 16V K
C783	QETN1HM-105Z	E CAPACITOR	1uF 50V M
C789	QETN1HM-476Z	E CAPACITOR	47uF 50V M
C790	NDC31HJ-270X	C CAPACITOR	27pF 50V J
C792	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C793	QETN1HM-335Z	E CAPACITOR	3.3uF 50V M
C802	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C803	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C804	QETN1CM-477Z	E CAPACITOR	470uF 16V M
C806	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C807	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
⚠C901	QFZ9077-104	MPP CAPACITOR	0.1uF 250V M
⚠C902	QFZ9072-473	MM CAPACITOR	0.047uF AC250V K
⚠C903	QCZ9015-102Z	C CAPACITOR	1000pF AC250V Z
⚠C904	QCZ9015-102Z	C CAPACITOR	1000pF AC250V Z
⚠C905	QCZ9015-102Z	C CAPACITOR	1000pF AC250V Z
C906	QEZ0649-227	E CAPACITOR	220uF 400V M
⚠C910	QFZ9077-104	MPP CAPACITOR	0.1uF 250V M
C915	QCZ0122-471	C CAPACITOR	470pF 2kV K
C917	QCB32HK-181Z	C CAPACITOR	180pF 500V K
C922	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C924	QETN1HM-105Z	E CAPACITOR	1uF 50V M
C925	QETN1HM-226Z	E CAPACITOR	22uF 50V M
C926	QFLC1HJ-822Z	M CAPACITOR	8200pF 50V J
C928	QCB31HK-102Z	C CAPACITOR	1000pF 50V K
C929	QCB32HK-103	C CAPACITOR	0.01uF 500V K
C931	QCZ0364-102	C CAPACITOR	1000pF 2kV K
C940	QCZ0364-152	C CAPACITOR	1500pF 2kV K
C949	QETN1AM-108Z	E CAPACITOR	1000uF 10V M
C950	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C951	QCZ0364-561	C CAPACITOR	560pF 2kV K
C952	QCB32HK-471Z	C CAPACITOR	470pF 500V K
C953	QCB32HK-471Z	C CAPACITOR	470pF 500V K
C955	QCB32HK-471Z	C CAPACITOR	470pF 500V K
C956	QEZ0203-107	E CAPACITOR	100uF 160V M
C957	QETN1CM-108Z	E CAPACITOR	1000uF 16V M
C958	QETN1EM-477Z	E CAPACITOR	470uF 25V M
C960	QETM1VM-228	E CAPACITOR	2200uF 35V M
C962	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C963	NCB31HK-102X	C CAPACITOR	1000pF 50V K
C964	QETN1VM-107Z	E CAPACITOR	100uF 35V M
C965	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C966	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C967	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C968	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C975	QETN1CM-477Z	E CAPACITOR	470uF 16V M
C976	NCB31HK-472X	C CAPACITOR	4700pF 50V K
C977	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C978	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C979	QETN1EM-107Z	E CAPACITOR	100uF 25V M
C980	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C981	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C982	QETN1HM-475Z	E CAPACITOR	4.7uF 50V M
C983	QETN1CM-106Z	E CAPACITOR	10uF 16V M
C984	QETN1HM-336Z	E CAPACITOR	33uF 50V M
C985	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C986	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C989	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
⚠C991	QCZ9079-102	C CAPACITOR	1000pF AC250V M
⚠C992	QCZ9079-102	C CAPACITOR	1000pF AC250V M
⚠C993	QCZ9079-102	C CAPACITOR	1000pF AC250V M
C994	QETN1HM-335Z	E CAPACITOR	3.3uF 50V M
R001	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R002	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R003	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R004	NRSA63J-273X	MG RESISTOR	27kΩ 1/16W J
R005	NRSA63J-820X	MG RESISTOR	82Ω 1/16W J

Digitized in Heiloo Netherland

⚠Ref No.	Part No.	Part Name	Description Local
R101	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R102	NRSA63J-822X	MG RESISTOR	8.2kΩ 1/16W J
R103	NRSA63J-182X	MG RESISTOR	1.8kΩ 1/16W J
R104	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R105	NRSA63J-220X	MG RESISTOR	22Ω 1/16W J
R106	NRSA63J-270X	MG RESISTOR	27Ω 1/16W J
R315	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R316	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R317	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R323	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R324	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R325	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R327	NRSA63J-334X	MG RESISTOR	330kΩ 1/16W J
R328	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R341	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R343	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R344	NRSA63J-220X	MG RESISTOR	22Ω 1/16W J
R345	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R351	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R352	NRSA63J-151X	MG RESISTOR	150Ω 1/16W J
R353	NRSA63J-151X	MG RESISTOR	150Ω 1/16W J
R354	NRSA63J-151X	MG RESISTOR	150Ω 1/16W J
R355	QRE121J-222Y	C RESISTOR	2.2kΩ 1/2W J
R356	QRE121J-222Y	C RESISTOR	2.2kΩ 1/2W J
R357	QRE121J-222Y	C RESISTOR	2.2kΩ 1/2W J
R358	QRZ0107-152Z	C RESISTOR	1.5kΩ 1/2W K
R359	QRZ0107-152Z	C RESISTOR	1.5kΩ 1/2W K
R360	QRZ0107-152Z	C RESISTOR	1.5kΩ 1/2W K
R369	QRE121J-124Y	C RESISTOR	120kΩ 1/2W J
R370	QRE121J-394Y	C RESISTOR	390kΩ 1/2W J
R411	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R412	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R426	NRSA63J-123X	MG RESISTOR	12kΩ 1/16W J
R427	NRSA63J-682X	MG RESISTOR	6.8kΩ 1/16W J
R430	NRSA63J-123X	MG RESISTOR	12kΩ 1/16W J
R432	QRX01GJ-2R7	MF RESISTOR	2.7Ω 1W J
R433	QRE121J-8R2Y	C RESISTOR	8.2Ω 1/2W J
R434	NRSA63J-682X	MG RESISTOR	6.8kΩ 1/16W J
R440	QRG01GJ-221	OMF RESISTOR	220Ω 1W J
R448	QRE121J-1R0Y	C RESISTOR	1Ω 1/2W J
R471	NRSA63J-155X	MG RESISTOR	1.5MΩ 1/16W J
R472	NRSA63J-124X	MG RESISTOR	120kΩ 1/16W J
R473	NRSA63J-683X	MG RESISTOR	68kΩ 1/16W J
R474	NRSA63J-224X	MG RESISTOR	220kΩ 1/16W J
R520	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R521	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R522	QRE121J-220Y	C RESISTOR	22Ω 1/2W J
R523	QRL029J-271	OMF RESISTOR	270Ω 2W J
R524	QRL039J-470	OMF RESISTOR	47Ω 3W J
R527	QRL039J-393	OMF RESISTOR	39kΩ 3W J
R528	QRE121J-471Y	C RESISTOR	470Ω 1/2W J
⚠R530	QRZ9017-4R7	FUSI RESISTOR	4.7Ω 1/4W J
⚠R533	QRZ9017-4R7	FUSI RESISTOR	4.7Ω 1/4W J
R551	QRX029J-R47	MF RESISTOR	0.47Ω 2W J
R552	QRX029J-R47	MF RESISTOR	0.47Ω 2W J
R554	NRSA63J-182X	MG RESISTOR	1.8kΩ 1/16W J
R569	QRZ0225-2R2	UNF RESISTOR	2.2Ω 7W K
R572	QRE121J-222Y	C RESISTOR	2.2kΩ 1/2W J
R573	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R574	QRE121J-183Y	C RESISTOR	18kΩ 1/2W J
R575	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R581	QRE121J-822Y	C RESISTOR	8.2kΩ 1/2W J
R582	QRE121J-154Y	C RESISTOR	150kΩ 1/2W J
R583	QRE121J-184Y	C RESISTOR	180kΩ 1/2W J
R601	NRSA63J-272X	MG RESISTOR	2.7kΩ 1/16W J
R602	NRSA63J-272X	MG RESISTOR	2.7kΩ 1/16W J
R603	MA111-X	SI DIODE	
R604	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R606	QRE121J-2R2Y	C RESISTOR	2.2Ω 1/2W J
R607	QRE121J-2R2Y	C RESISTOR	2.2Ω 1/2W J
R609	NRSA63J-273X	MG RESISTOR	27kΩ 1/16W J
R610	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R611	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R612	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R614	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R618	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R620	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R621	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R622	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R623	NRSA63J-333X	MG RESISTOR	33kΩ 1/16W J
R624	NRSA63J-683X	MG RESISTOR	68kΩ 1/16W J
R626	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R629	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R630	QRE121J-271Y	C RESISTOR	270Ω 1/2W J
R631	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R632	QRE121J-271Y	C RESISTOR	270Ω 1/2W J
R633	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R634	NRSA63J-271X	MG RESISTOR	270Ω 1/16W J
R636	NRSA63J-271X	MG RESISTOR	270Ω 1/16W J
R637	NRSA63J-472X	MG RESISTOR	4.7kΩ 1/16W J
R639	NRSA63J-472X	MG RESISTOR	4.7kΩ 1/16W J
R640	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R701	NRSA63J-123X	MG RESISTOR	12kΩ 1/16W J
R702	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R703	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R704	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R705	NRSA63J-393X	MG RESISTOR	39kΩ 1/16W J
R706	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R707	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R708	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R709	NRSA63J-105X	MG RESISTOR	1MΩ 1/16W J
R711	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R712	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R713	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R714	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R715	NRSA63J-391X	MG RESISTOR	390Ω 1/16W J
R716	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R717	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R718	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R719	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R726	NRSA63J-273X	MG RESISTOR	27kΩ 1/16W J
R727	NRSA63J-561X	MG RESISTOR	560Ω 1/16W J
R728	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R731	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R732	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R733	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R734	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R735	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R736	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R737	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R738	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R740	NRSA63J-153X	MG RESISTOR	15kΩ 1/16W J
R741	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R742	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R743	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R744	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R745	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R747	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R748	NRSA63J-272X	MG RESISTOR	2.7kΩ 1/16W J
R749	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R751	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R752	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R753	NRSA63J-122X	MG RESISTOR	1.2kΩ 1/16W J
R754	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R755	NRSA63J-122X	MG RESISTOR	1.2kΩ 1/16W J
R756	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R757	NRSA63J-472X	MG RESISTOR	4.7kΩ 1/16W J
R758	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R759	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R760	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R761	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R762	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R763	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R764	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R765	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R768	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R771	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R772	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R773	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R774	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R775	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R776	NRSA63J-153X	MG RESISTOR	15kΩ 1/16W J
R777	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R779	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R780	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R781	NRSA63J-472X	MG RESISTOR	4.7kΩ 1/16W J
R782	NRSA63J-122X	MG RESISTOR	1.2kΩ 1/16W J
R783	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R785	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R786	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R790	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R791	QRE121J-102Y	C RESISTOR	1kΩ 1/2W J
R792	QRE123J-330X	C RESISTOR	33Ω 1/2W J
R793	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R794	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R795	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R796	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R801	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R802	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R803	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R804	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R805	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R806	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R807	QRE121J-101Y	C RESISTOR	100Ω 1/2W J

Digitized in Heiloo Netherland

www.freeservicemanuals.info

⚠Ref No.	Part No.	Part Name	Description Local
R809	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R810	NRSA63J-391X	MG RESISTOR	390Ω 1/16W J
R811	NRSA63J-823X	MG RESISTOR	82kΩ 1/16W J
R812	NRSA63J-391X	MG RESISTOR	390Ω 1/16W J
R813	NRSA63J-823X	MG RESISTOR	82kΩ 1/16W J
R814	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R815	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R816	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R818	NRSA63J-181X	MG RESISTOR	180Ω 1/16W J
R819	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R820	NRSA63J-331X	MG RESISTOR	330Ω 1/16W J
R821	NRSA63J-471X	MG RESISTOR	470Ω 1/16W J
R822	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R823	QRE121J-470Y	C RESISTOR	47Ω 1/2W J
R824	NRSA63J-471X	MG RESISTOR	470Ω 1/16W J
R901	QRF154K-2R2	UNF WW RESISTOR	2.2Ω 15W K
R902	QRL029J-473	OMF RESISTOR	47kΩ 2W J
R903	QRL029J-333	OMF RESISTOR	33kΩ 2W J
⚠R910	QRZ0107-474Z	C RESISTOR	470kΩ 1/2W K
R921	QRE121J-101Y	C RESISTOR	100Ω 1/2W J
R922	QRZ0237-R18	UNF WW RESISTOR	0.18Ω 3W J
R923	QRT029J-R47	MF RESISTOR	0.47Ω 2W J
R924	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R929	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R930	QRL039J-473	OMF RESISTOR	47kΩ 3W J
⚠R932	QRZ9017-100	FUSI RESISTOR	10Ω 1/4W J
R934	QRE121J-102Y	C RESISTOR	1kΩ 1/2W J
R935	QRE121J-152Y	C RESISTOR	1.5kΩ 1/2W J
R951	QRE121J-102Y	C RESISTOR	1kΩ 1/2W J
R953	QRE121J-182Y	C RESISTOR	1.8kΩ 1/2W J
R962	QRL029J-223	OMF RESISTOR	22kΩ 2W J
R963	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R964	NRSA63J-473X	MG RESISTOR	47kΩ 1/16W J
R965	QRT029J-R82	MF RESISTOR	0.82Ω 2W J
R970	QRE121J-182Y	C RESISTOR	1.8kΩ 1/2W J
R973	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R974	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R976	NRSA63J-391X	MG RESISTOR	390Ω 1/16W J
R977	QRL039J-120	OMF RESISTOR	12Ω 3W J
R978	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R981	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
⚠R991	QRZ9046-825Z	C RESISTOR	8.2MΩ 1/2W K
L002	QQL244J-4R7Z	PEAKING COIL	4.7uH J
L003	QQL244J-4R7Z	PEAKING COIL	4.7uH J
L101	QQL244K-1R0Z	PEAKING COIL	1uH K
L351	QQL244J-220Z	COIL	22uH J
L522	QQR1005-004	LINEARITY COIL	
L551	QQLZ034-280	HEATER CHOKE	28uH
L701	NQL092K-100X	COIL	10uH K
L702	NQL092K-100X	COIL	10uH K
L703	NQL092K-100X	COIL	10uH K
L704	NQL092K-100X	COIL	10uH K
L705	NQL092K-100X	COIL	10uH K
L706	NQL092K-100X	COIL	10uH K
L707	NQL092K-100X	COIL	10uH K
L708	NQL092K-100X	COIL	10uH K
L709	NQL092K-100X	COIL	10uH K
L710	NQL092K-100X	COIL	10uH K
L711	NQL092K-100X	COIL	10uH K
L712	NQL092K-100X	COIL	10uH K
L713	NQL092K-100X	COIL	10uH K
L714	NRSA02J-0R0X	MG RESISTOR	0Ω 1/10W J
L715	NQL092K-100X	COIL	10uH K
L716	NQL092K-100X	COIL	10uH K
L717	NQL092K-100X	COIL	10uH K
L951	QQLZ034-460	HEATER CHOKE	46uH
L952	QQL26AK-470Z	CHOKE COIL	47uH K
L954	QQL244J-5R6Z	COIL	5.6uH J
L972	QQL244J-5R6Z	COIL	5.6uH J
L973	QQL244J-5R6Z	COIL	5.6uH J
L975	QQL26AK-820Z	CHOKE COIL	82uH K
L994	NRSA02J-0R0X	MG RESISTOR	0Ω 1/10W J
T521	QQR1522-001	DRIVE TRANSF	
⚠T921	QQS0271-001	SW TRANSF	
⚠PC901	PS2581AL1/QW/	PHOTO COUPLER	
CF101	QAX0349-001	C TRAP	47.25MHz
⚠CP650	ICP-N25-Y	IC PROTECTOR	1.0A
⚠CP952	ICP-N38-Y	IC PROTECTOR	1.5A
⚠CP953	ICP-N38-Y	IC PROTECTOR	1.5A
⚠CP955	ICP-N75-Y	IC PROTECTOR	2.7A
⚠F901	QMF51E2-4R0J4	FUSE	4A AC250V
J801	QNZ0454-002	PIN JACK	VIDEO1/S-VIDEO
J802	QNN0349-002	PIN JACK	VIDEO2/COMP
J803	QNN0348-001	PIN JACK	VIDEO2/COMP

⚠Ref No.	Part No.	Part Name	Description Local
J804	QNN0349-001	PIN JACK	VIDEO OUT
J806	QNN0281-003	PIN JACK	VIDEO3(FRONT)/L3
J807	QNN0281-002	PIN JACK	VIDEO3(FRONT)/R3
J808	QNN0282-001	PIN JACK	VIDEO3(FRONT)/V3
J809	QNS0155-001	3.5 JACK	HEADPHONE
K101	QQR1114-001Z	FERRITE BEADS	
K103	QQR1114-001Z	FERRITE BEADS	
K107	QQR1114-001Z	FERRITE BEADS	
K108	QQR1114-001Z	FERRITE BEADS	
K355	QQR1113-001Z	FERRITE BEADS	
K901	QQR1114-001Z	FERRITE BEADS	
K921	QQR1114-001Z	FERRITE BEADS	
K922	QQR1114-001Z	FERRITE BEADS	
K951	QQR1114-001Z	FERRITE BEADS	
K952	QQR1113-001Z	FERRITE BEADS	
K953	QQR1113-001Z	FERRITE BEADS	
K955	QQR1113-001Z	FERRITE BEADS	
LC801	QQR1199-001	EMI FILTER	
LC802	QQR1199-001	EMI FILTER	
LC803	QQR1199-001	EMI FILTER	
LC804	QQR1199-001	EMI FILTER	
LC805	QQR1199-001	EMI FILTER	
⚠LF901	QQR0673-004	LINE FILTER	
⚠LF902	QQR1035-002	LINE FILTER	
⚠RY901	QSK0061-002	RELAY	
S801	QSW0619-003Z	TACT SWITCH	MENU
S802	QSW0619-003Z	TACT SWITCH	CH-
S803	QSW0619-003Z	TACT SWITCH	CH+
S804	QSW0619-003Z	TACT SWITCH	VOL-
S805	QSW0619-003Z	TACT SWITCH	VOL+
⚠S901	QSW0750-001	PUSH SWITCH	POWER
SF102	QAX0723-001	SAW FILTER	
⚠SK351	QNZ0536-001	CRT SOCKET	
⚠TH901	QAD0134-4R5	P THERMISTOR	4.5Ω
TU001	QAU0353-001	TUNER	
⚠VA901	QAF0060-621	VARISTOR	620V
X701	QAX0799-001Z	CRYSTAL	
	LC30114-001C-H	LED HOLDER	
	LC41232-001A-H	EE HOLDER	

Digitized in Heiloo Netherland

PRINTED WIRING BOARD PARTS LIST [AV-21VT34/P]

MAIN P.W. BOARD ASS'Y (SCW-1038A-H2)

⚠Ref No.	Part No.	Part Name	Description Local
IC302	S9066-11	PHOTO CONDUCTOR	
IC351	TDA6107AJF/N1	IC	
IC401	AN15525A	IC	
IC601	AN7585	IC	
IC651	RC4558D-X	IC	
IC701	TDA12027-NTSC	IC(MCU)	(SERVICE)
IC702	AT24C16-21VT34P	IC	(SERVICE)
IC801	RPM7238-H5	IR DETECT UNIT	
IC921	STR-W6756-F5	SW IC	
IC951	SE135N	IC	
IC972	BA33BC0T	REGULATOR IC	
IC973	PQ120RDA1SZ	IC	
IC974	MM1561JF-X	IC	
IC975	PQ050RDA1SZ	IC	
IC976	MM1561JF-X	IC	
Q001	2SK1374-X	MOS FET	
Q002	2SK1374-X	MOS FET	
Q101	2SC5083/L-P/-T	TRANSISTOR	
Q341	2SA1530A/QR/-X	TRANSISTOR	
Q521	2SC2655/Y/-T	TRANSISTOR	
⚠Q522	TT2190LS-YB11	TRANSISTOR	
Q571	2SA1208/ST/Z1-T	TRANSISTOR	
Q572	UN2212-X	DIGI TRANSISTOR	
Q601	2SA1530A/QR/-X	TRANSISTOR	
Q602	2SA1530A/QR/-X	TRANSISTOR	
Q603	DTC323TK-X	DIGI TRANSISTOR	
Q604	UN2212-X	DIGI TRANSISTOR	
Q605	DTC323TK-X	DIGI TRANSISTOR	
Q606	UN2212-X	DIGI TRANSISTOR	
Q607	2SC3928A/QR/-X	TRANSISTOR	
Q608	2SC3928A/QR/-X	TRANSISTOR	
Q609	UN2212-X	DIGI TRANSISTOR	
Q610	UN2212-X	DIGI TRANSISTOR	
Q611	UN2212-X	DIGI TRANSISTOR	
Q612	2SC1740S/QR/-T	TRANSISTOR	
Q703	2SA1530A/QR/-X	TRANSISTOR	
Q704	2SC3928A/QR/-X	TRANSISTOR	
Q705	SSM3K02F-X	MOS FET	
Q706	SSM3K02F-X	MOS FET	
Q707	2SC3928A/QR/-X	TRANSISTOR	
Q708	2SA1530A/QR/-X	TRANSISTOR	
Q791	DTC124ESA-T	DIGI TRANSISTOR	
Q801	KTA1267/YG/-T	TRANSISTOR	
Q803	DTC323TK-X	DIGI TRANSISTOR	
Q804	DTC323TK-X	DIGI TRANSISTOR	
Q805	2SA1530A/QR/-X	TRANSISTOR	
Q955	2SC3928A/QR/-X	TRANSISTOR	
D001	MA8051/M/-X	Z DIODE	
D341	MA8033/H/-X	Z DIODE	
D342	MA8033/H/-X	Z DIODE	
D343	MA8033/H/-X	Z DIODE	
D345	MA111-X	SI DIODE	
D349	MA8120/M/-X	Z DIODE	
D350	MA8075/M/-X	Z DIODE	
D351	EU01N-T2	SI DIODE	
D354	RGP10J-5025-T3	SI DIODE	
D355	RGP10J-5025-T3	SI DIODE	
D356	RGP10J-5025-T3	SI DIODE	
D422	MTZJ75-T2	Z DIODE	
D423	1N4003-T2	SI DIODE	
D471	1SR124-400A-T2	SI DIODE	
D472	MA111-X	SI DIODE	
D520	MA111-X	SI DIODE	
D521	ERB06-15-F1	SI DIODE	
D522	RU3AM-LFC4	SI DIODE	
D523	RGP10J-5025-T3	SI DIODE	
D530	RGP10J-5025-T3	SI DIODE	
D551	RGP10J-5025-T3	SI DIODE	
D552	RGP10J-5025-T3	SI DIODE	
D554	MA8051/L/-X	Z DIODE	
D571	MA8075/H/-X	Z DIODE	
D581	RGP10J-5025-T3	SI DIODE	
D601	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
D602	1SS133-T2	SI DIODE	
D603	MA111-X	SI DIODE	
D604	MA8300/H/-X	Z DIODE	
D605	MA8300/H/-X	Z DIODE	
D606	MA8300/H/-X	Z DIODE	
D607	1SS133-T2	SI DIODE	
D651	MA8062/M/-X	Z DIODE	
D701	MA111-X	SI DIODE	
D702	MA8091/H/-X	Z DIODE	
D704	MA8091/H/-X	Z DIODE	
D706	MTZJ4.3A-T2	Z DIODE	
D707	MA111-X	SI DIODE	
D708	MA111-X	SI DIODE	
D709	MA111-X	SI DIODE	
D710	MA8091/H/-X	Z DIODE	
D711	MA8051/M/-X	Z DIODE	
D712	MA8051/M/-X	Z DIODE	
D713	MA8039/H/-X	Z DIODE	
D714	MA8030/H/-X	Z DIODE	
D751	MA8091/H/-X	Z DIODE	
D753	MA8091/H/-X	Z DIODE	
D791	MA8062/M/-X	Z DIODE	
D801	NCB31HK-152X	C CAPACITOR	1500pF 50V K
D802	NCB31HK-152X	C CAPACITOR	1500pF 50V K
D803	NCB31HK-152X	C CAPACITOR	1500pF 50V K
D804	NCB31HK-152X	C CAPACITOR	1500pF 50V K
D808	LH22440-T16	LED	POWER(RED)
D810	MA8091/H/-X	Z DIODE	
D811	MA8091/H/-X	Z DIODE	
D812	MA8091/H/-X	Z DIODE	
D813	MA8091/H/-X	Z DIODE	
D814	MA8091/H/-X	Z DIODE	
D815	NCB31HK-152X	C CAPACITOR	1500pF 50V K
D816	NCB31HK-152X	C CAPACITOR	1500pF 50V K
D817	MA8091/H/-X	Z DIODE	
D901	GSIB460	BRIDGE DIODE	
D921	RGP10J-5025-T3	SI DIODE	
D922	1SS133-T2	SI DIODE	
D926	RGP10M-5010-T3	SI DIODE	
D927	1SS133-T2	SI DIODE	
D928	MA8240/M/-X	Z DIODE	
D929	MA111-X	SI DIODE	
D931	MA8062/M/-X	Z DIODE	
D932	MTZJ27B-T2	Z DIODE	
D933	MTZJ9.1C-T2	Z DIODE	
D934	MTZJ9.1C-T2	Z DIODE	
D935	MTZJ9.1C-T2	Z DIODE	
D951	31DF6N-FC5	SI DIODE	
D952	FSF05A20	SI DIODE	
D953	RGP10J-5025-T3	SI DIODE	
D955	FSF05A20	SI DIODE	
D956	MA111-X	SI DIODE	
D957	MA111-X	SI DIODE	
D962	MA8330/M/-X	Z DIODE	
D970	MA8082/M/-X	Z DIODE	
D971	MA111-X	SI DIODE	
D973	MA111-X	SI DIODE	
D975	MA111-X	SI DIODE	
D977	MA111-X	SI DIODE	
D980	QQR1114-001Z	FERRITE BEADS	
C001	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C002	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C003	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C004	QETN1CM-477Z	E CAPACITOR	470uF 16V M
C005	NCB31HK-222X	C CAPACITOR	2200pF 50V K
C006	QETN1CM-336Z	E CAPACITOR	33uF 16V M
C101	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C102	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C103	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C104	QETN1EM-476Z	E CAPACITOR	47uF 25V M
C106	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C109	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
C110	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C111	QETN1CM-477Z	E CAPACITOR	470uF 16V M
C317	QETN1HM-105Z	E CAPACITOR	1uF 50V M
C341	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C351	NDC21HJ-102X	C CAPACITOR	1000pF 50V J
C352	QETN2EM-475Z	E CAPACITOR	4.7uF 250V M
C353	QFKC2EK-104Z	MM CAPACITOR	0.1uF 250V K
C358	QCZ0364-152	C CAPACITOR	1500pF 2kV K
C422	QCS32HJ-180Z	C CAPACITOR	18pF 500V J
C423	NCB31HK-682X	C CAPACITOR	6800pF 50V K
C424	QFLC2AJ-683Z	M CAPACITOR	0.068uF 100V J
C427	QETM1VM-108	E CAPACITOR	1000uF 35V M
C428	QEHR1VM-227Z	E CAPACITOR	220uF 35V M
C430	QFLC2AJ-563Z	M CAPACITOR	0.056uF 100V J
C431	QFVF1HJ-184Z	MF CAPACITOR	0.18uF 50V J
C435	NCF21HZ-334X	C CAPACITOR	0.33uF 50V Z
C436	NCF21HZ-334X	C CAPACITOR	0.33uF 50V Z
C471	QETN1HM-106Z	E CAPACITOR	10uF 50V M

Digitized in Heiloo Netherland

⚠Ref No.	Part No.	Part Name	Description Local
C520	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C521	QCB31HK-332Z	C CAPACITOR	3300pF 50V K
C522	QFLC1HJ-223Z	M CAPACITOR	0.022uF 50V J
C523	QETN1VM-476Z	E CAPACITOR	47uF 35V M
⚠C524	QFZ0196-202	MPP CAPACITOR	2000pF 1.5kV H
C525	QFZ0196-502	MPP CAPACITOR	5000pF 1.5kV H
C526	QFZ0196-202	MPP CAPACITOR	2000pF 1.5kV H
C527	QFZ0197-124	MPP CAPACITOR	0.12uF 250V J
C528	QFP32GJ-393	PP CAPACITOR	0.039uF 400V J
C529	QETN2EM-475Z	E CAPACITOR	4.7uF 250V M
C530	QCB32HK-561Z	C CAPACITOR	560pF 500V K
C532	QETN2EM-106Z	E CAPACITOR	10uF 250V M
C551	QCB32HK-561Z	C CAPACITOR	560pF 500V K
C552	QCB32HK-561Z	C CAPACITOR	560pF 500V K
C553	QEHR1EM-108Z	E CAPACITOR	1000uF 25V M
C554	QEHR1EM-108Z	E CAPACITOR	1000uF 25V M
C555	QFLC2AJ-103Z	M CAPACITOR	0.01uF 100V J
C571	QEZ0203-107	E CAPACITOR	100uF 160V M
C572	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C573	QETN1EM-476Z	E CAPACITOR	47uF 25V M
C581	QFVF1HJ-104Z	MF CAPACITOR	0.1uF 50V J
C582	QFZ0197-124	MPP CAPACITOR	0.12uF 250V J
C601	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C602	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C603	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C604	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C605	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C606	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C607	QETN1CM-227Z	E CAPACITOR	220uF 16V M
C608	QETN1CM-227Z	E CAPACITOR	220uF 16V M
C609	QETN1HM-336Z	E CAPACITOR	33uF 50V M
C610	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C611	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C612	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C613	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C614	QETM1VM-228	E CAPACITOR	2200uF 35V M
C615	QETM1VM-108	E CAPACITOR	1000uF 35V M
C616	QETM1VM-108	E CAPACITOR	1000uF 35V M
C651	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C652	NDC31HJ-101X	C CAPACITOR	100pF 50V J
C653	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C654	QETN1HM-475Z	E CAPACITOR	4.7uF 50V M
C655	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C656	QETN1HM-107Z	E CAPACITOR	100uF 50V M
C657	QENC1HM-106Z	BP E CAPACITOR	10uF 50V M
C658	QENC1HM-106Z	BP E CAPACITOR	10uF 50V M
C660	NCB21EK-124X	C CAPACITOR	0.12uF 25V K
C661	QETN1CM-227Z	E CAPACITOR	220uF 16V M
C662	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C701	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C702	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C703	QETN1CM-477Z	E CAPACITOR	470uF 16V M
C704	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C705	NDC31HJ-3R0X	C CAPACITOR	3pF 50V J
C706	NDC31HJ-3R0X	C CAPACITOR	3pF 50V J
C707	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C708	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C709	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C710	NCB31HK-682X	C CAPACITOR	6800pF 50V K
C711	QETN1HM-225Z	E CAPACITOR	2.2uF 50V M
C712	QFVF1HJ-224Z	MF CAPACITOR	0.22uF 50V J
C713	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C714	NCB31HK-223X	C CAPACITOR	0.022uF 50V K
C715	NCB31HK-102X	C CAPACITOR	1000pF 50V K
C716	NCB31HK-102X	C CAPACITOR	1000pF 50V K
C717	NCB31HK-473X	C CAPACITOR	0.047uF 50V K
C718	QFVF1HJ-104Z	MF CAPACITOR	0.1uF 50V J
C719	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C720	NCB31HK-102X	C CAPACITOR	1000pF 50V K
C723	NCB21CK-105X	C CAPACITOR	1uF 16V K
C724	NCB21CK-105X	C CAPACITOR	1uF 16V K
C726	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C727	NCB31HK-332X	C CAPACITOR	3300pF 50V K
C728	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C729	QETN1HM-225Z	E CAPACITOR	2.2uF 50V M
C730	QETN1HM-226Z	E CAPACITOR	22uF 50V M
C731	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C732	QETN1HM-225Z	E CAPACITOR	2.2uF 50V M
C733	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C734	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C735	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C736	NCB31HK-103X	C CAPACITOR	0.01uF 50V K
C737	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C738	NCB21CK-105X	C CAPACITOR	1uF 16V K
C739	NCB21CK-105X	C CAPACITOR	1uF 16V K
C740	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C741	NCB31HK-104X	C CAPACITOR	0.1uF 50V K

⚠Ref No.	Part No.	Part Name	Description Local
C742	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C743	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C744	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C745	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C746	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C747	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C748	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C749	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C750	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C751	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C752	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C753	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C754	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C755	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C756	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C757	NDC31HJ-561X	C CAPACITOR	560pF 50V J
C758	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C759	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C760	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C761	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C762	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C763	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C764	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C765	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C766	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C767	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C768	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C770	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C771	QETN1HM-226Z	E CAPACITOR	22uF 50V M
C772	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C773	QETN1HM-225Z	E CAPACITOR	2.2uF 50V M
C774	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C775	NCB31CK-224X	C CAPACITOR	0.22uF 16V K
C776	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C777	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C778	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C779	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C780	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C781	NCB21CK-105X	C CAPACITOR	1uF 16V K
C782	NCB21CK-105X	C CAPACITOR	1uF 16V K
C783	QETN1HM-105Z	E CAPACITOR	1uF 50V M
C789	QETN1HM-476Z	E CAPACITOR	47uF 50V M
C790	NDC31HJ-270X	C CAPACITOR	27pF 50V J
C792	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C793	QETN1HM-335Z	E CAPACITOR	3.3uF 50V M
C802	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C803	QETN1HM-106Z	E CAPACITOR	10uF 50V M
C804	QETN1CM-477Z	E CAPACITOR	470uF 16V M
C806	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C807	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
⚠C901	QFZ9077-104	MPP CAPACITOR	0.1uF 250V M
⚠C902	QFZ9072-473	MM CAPACITOR	0.047uF AC250V K
⚠C903	QCZ9015-102Z	C CAPACITOR	1000pF AC250V Z
⚠C904	QCZ9015-102Z	C CAPACITOR	1000pF AC250V Z
⚠C905	QCZ9015-102Z	C CAPACITOR	1000pF AC250V Z
C906	QEZ0649-227	E CAPACITOR	220uF 400V M
⚠C910	QFZ9072-104	MM CAPACITOR	0.1uF AC250V K
C915	QCZ0122-471	C CAPACITOR	470pF 2kV K
C917	QCB32HK-181Z	C CAPACITOR	180pF 500V K
C922	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C924	QETN1HM-105Z	E CAPACITOR	1uF 50V M
C925	QETN1HM-226Z	E CAPACITOR	22uF 50V M
C926	QFLC1HJ-822Z	M CAPACITOR	8200pF 50V J
C928	QCB31HK-102Z	C CAPACITOR	1000pF 50V K
C929	QCB32HK-103	C CAPACITOR	0.01uF 500V K
C931	QCZ0364-102	C CAPACITOR	1000pF 2kV K
C940	QCZ0364-152	C CAPACITOR	1500pF 2kV K
C949	QETN1AM-108Z	E CAPACITOR	1000uF 10V M
C950	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C951	QCZ0364-561	C CAPACITOR	560pF 2kV K
C952	QCB32HK-471Z	C CAPACITOR	470pF 500V K
C953	QCB32HK-471Z	C CAPACITOR	470pF 500V K
C955	QCB32HK-471Z	C CAPACITOR	470pF 500V K
C956	QEZ0203-107	E CAPACITOR	100uF 160V M
C957	QETN1CM-108Z	E CAPACITOR	1000uF 16V M
C958	QETN1EM-477Z	E CAPACITOR	470uF 25V M
C960	QETM1VM-228	E CAPACITOR	2200uF 35V M
C962	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C963	NCB31HK-102X	C CAPACITOR	1000pF 50V K
C964	QETN1VM-107Z	E CAPACITOR	100uF 35V M
C965	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C966	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C967	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C968	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C975	QETN1CM-477Z	E CAPACITOR	470uF 16V M
C976	NCB31HK-472X	C CAPACITOR	4700pF 50V K
C977	QETN1CM-476Z	E CAPACITOR	47uF 16V M

Digitized in Heiloo Netherland

www.freeservicemanuals.info

⚠Ref No.	Part No.	Part Name	Description Local
C978	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C979	QETN1EM-107Z	E CAPACITOR	100uF 25V M
C980	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C981	QETN1CM-107Z	E CAPACITOR	100uF 16V M
C983	QETN1CM-106Z	E CAPACITOR	10uF 16V M
C984	QETN1HM-336Z	E CAPACITOR	33uF 50V M
C985	QETN1CM-476Z	E CAPACITOR	47uF 16V M
C986	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
C989	NCB31HK-104X	C CAPACITOR	0.1uF 50V K
⚠C991	QCZ9079-102	C CAPACITOR	1000pF AC250V M
⚠C992	QCZ9079-102	C CAPACITOR	1000pF AC250V M
⚠C993	QCZ9079-102	C CAPACITOR	1000pF AC250V M
C994	QETN1HM-335Z	E CAPACITOR	3.3uF 50V M
R001	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R002	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R003	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R004	NRSA63J-273X	MG RESISTOR	27kΩ 1/16W J
R005	NRSA63J-820X	MG RESISTOR	82Ω 1/16W J
R006	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R007	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R008	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R101	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R102	NRSA63J-822X	MG RESISTOR	8.2kΩ 1/16W J
R103	NRSA63J-182X	MG RESISTOR	1.8kΩ 1/16W J
R104	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R105	NRSA63J-220X	MG RESISTOR	22Ω 1/16W J
R106	NRSA63J-270X	MG RESISTOR	27Ω 1/16W J
R315	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R316	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R317	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R323	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R324	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R325	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R327	NRSA63J-334X	MG RESISTOR	330kΩ 1/16W J
R328	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R341	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R343	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R344	NRSA63J-220X	MG RESISTOR	22Ω 1/16W J
R345	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R351	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R352	NRSA63J-151X	MG RESISTOR	150Ω 1/16W J
R353	NRSA63J-151X	MG RESISTOR	150Ω 1/16W J
R354	NRSA63J-151X	MG RESISTOR	150Ω 1/16W J
R355	QRE121J-222Y	C RESISTOR	2.2kΩ 1/2W J
R356	QRE121J-222Y	C RESISTOR	2.2kΩ 1/2W J
R357	QRE121J-222Y	C RESISTOR	2.2kΩ 1/2W J
R358	QRZ0107-152Z	C RESISTOR	1.5kΩ 1/2W K
R359	QRZ0107-152Z	C RESISTOR	1.5kΩ 1/2W K
R360	QRZ0107-152Z	C RESISTOR	1.5kΩ 1/2W K
R369	QRE121J-124Y	C RESISTOR	120kΩ 1/2W J
R370	QRE121J-394Y	C RESISTOR	390kΩ 1/2W J
R411	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R412	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R426	NRSA63J-123X	MG RESISTOR	12kΩ 1/16W J
R427	NRSA63J-682X	MG RESISTOR	6.8kΩ 1/16W J
R430	NRSA63J-123X	MG RESISTOR	12kΩ 1/16W J
R432	QRX01GJ-2R7	MF RESISTOR	2.7Ω 1W J
R433	QRE121J-8R2Y	C RESISTOR	8.2Ω 1/2W J
R434	NRSA63J-682X	MG RESISTOR	6.8kΩ 1/16W J
R440	QRG01GJ-221	OMF RESISTOR	220Ω 1W J
R448	QRE121J-1R0Y	C RESISTOR	1Ω 1/2W J
R471	NRSA63J-155X	MG RESISTOR	1.5MΩ 1/16W J
R472	NRSA63J-124X	MG RESISTOR	120kΩ 1/16W J
R473	NRSA63J-683X	MG RESISTOR	68kΩ 1/16W J
R474	NRSA63J-224X	MG RESISTOR	220kΩ 1/16W J
R520	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R521	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R522	QRE121J-220Y	C RESISTOR	22Ω 1/2W J
R523	QRL029J-271	OMF RESISTOR	270Ω 2W J
R524	QRL039J-470	OMF RESISTOR	47Ω 3W J
R527	QRL039J-393	OMF RESISTOR	39kΩ 3W J
R528	QRE121J-471Y	C RESISTOR	470Ω 1/2W J
⚠R530	QRZ9017-4R7	FUSI RESISTOR	4.7Ω 1/4W J
⚠R533	QRZ9017-4R7	FUSI RESISTOR	4.7Ω 1/4W J
R551	QRX029J-R47	MF RESISTOR	0.47Ω 2W J
R552	QRX029J-R47	MF RESISTOR	0.47Ω 2W J
R554	NRSA63J-182X	MG RESISTOR	1.8kΩ 1/16W J
R569	QRZ0225-2R2	UNF RESISTOR	2.2Ω 7W K
R572	QRE121J-222Y	C RESISTOR	2.2kΩ 1/2W J
R573	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R574	QRE121J-183Y	C RESISTOR	18kΩ 1/2W J
R575	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R581	QRE121J-822Y	C RESISTOR	8.2kΩ 1/2W J
R582	QRE121J-154Y	C RESISTOR	150kΩ 1/2W J
R583	QRE121J-184Y	C RESISTOR	180kΩ 1/2W J
R601	NRSA63J-272X	MG RESISTOR	2.7kΩ 1/16W J
R602	NRSA63J-272X	MG RESISTOR	2.7kΩ 1/16W J
R603	MA111-X	SI DIODE	
R604	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R605	NRSA63J-822X	MG RESISTOR	8.2kΩ 1/16W J
R606	QRE121J-2R2Y	C RESISTOR	2.2Ω 1/2W J
R607	QRE121J-2R2Y	C RESISTOR	2.2Ω 1/2W J
R609	NRSA63J-273X	MG RESISTOR	27kΩ 1/16W J
R610	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R611	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R612	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R613	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R614	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R615	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R618	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R619	NRSA63J-822X	MG RESISTOR	8.2kΩ 1/16W J
R620	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R621	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R622	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R623	NRSA63J-333X	MG RESISTOR	33kΩ 1/16W J
R624	NRSA63J-683X	MG RESISTOR	68kΩ 1/16W J
R625	QRE121J-2R2Y	C RESISTOR	2.2Ω 1/2W J
R626	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R629	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R630	QRE121J-271Y	C RESISTOR	270Ω 1/2W J
R631	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R632	QRE121J-271Y	C RESISTOR	270Ω 1/2W J
R633	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R634	NRSA63J-271X	MG RESISTOR	270Ω 1/16W J
R635	NRSA63J-271X	MG RESISTOR	270Ω 1/16W J
R636	NRSA63J-271X	MG RESISTOR	270Ω 1/16W J
R637	NRSA63J-472X	MG RESISTOR	4.7kΩ 1/16W J
R638	NRSA63J-472X	MG RESISTOR	4.7kΩ 1/16W J
R639	NRSA63J-472X	MG RESISTOR	4.7kΩ 1/16W J
R640	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R651	NRSA63J-122X	MG RESISTOR	1.2kΩ 1/16W J
R653	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R654	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R655	NRSA63J-333X	MG RESISTOR	33kΩ 1/16W J
R656	NRSA63J-333X	MG RESISTOR	33kΩ 1/16W J
R657	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R658	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R659	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R660	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R661	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R662	NRSA63J-272X	MG RESISTOR	2.7kΩ 1/16W J
R663	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R664	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R701	NRSA63J-123X	MG RESISTOR	12kΩ 1/16W J
R702	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R703	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R704	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R705	NRSA63J-393X	MG RESISTOR	39kΩ 1/16W J
R706	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R707	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R708	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R709	NRSA63J-105X	MG RESISTOR	1MΩ 1/16W J
R711	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R712	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R713	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R714	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R715	NRSA63J-391X	MG RESISTOR	390Ω 1/16W J
R716	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R717	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R718	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R719	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R720	QRE141J-152Y	C RESISTOR	1.5kΩ 1/4W J
R721	QRE141J-152Y	C RESISTOR	1.5kΩ 1/4W J
R726	NRSA63J-273X	MG RESISTOR	27kΩ 1/16W J
R727	NRSA63J-561X	MG RESISTOR	560Ω 1/16W J
R728	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R731	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R732	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R733	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R734	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R735	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R736	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R737	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R738	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R740	NRSA63J-153X	MG RESISTOR	15kΩ 1/16W J
R741	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R742	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R743	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R744	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R745	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R747	NRSA63J-153X	MG RESISTOR	15kΩ 1/16W J
R748	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R749	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J

Digitized in Heiloo Netherland

⚠Ref No.	Part No.	Part Name	Description Local
R751	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R752	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R753	NRSA63J-122X	MG RESISTOR	1.2kΩ 1/16W J
R754	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R755	NRSA63J-122X	MG RESISTOR	1.2kΩ 1/16W J
R756	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R757	NRSA63J-472X	MG RESISTOR	4.7kΩ 1/16W J
R758	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R759	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R760	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R761	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R762	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R763	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R764	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R765	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R768	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R771	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R772	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R773	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R774	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R775	NRSA63J-392X	MG RESISTOR	3.9kΩ 1/16W J
R776	NRSA63J-153X	MG RESISTOR	15kΩ 1/16W J
R777	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R779	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R780	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R781	NRSA63J-472X	MG RESISTOR	4.7kΩ 1/16W J
R782	NRSA63J-122X	MG RESISTOR	1.2kΩ 1/16W J
R783	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R785	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R786	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R787	QRE141J-472Y	C RESISTOR	4.7kΩ 1/4W J
R790	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R791	QRE121J-102Y	C RESISTOR	1kΩ 1/2W J
R792	QRE123J-330X	C RESISTOR	33Ω 1/2W J
R793	NRSA63J-101X	MG RESISTOR	100Ω 1/16W J
R794	NRSA63J-222X	MG RESISTOR	2.2kΩ 1/16W J
R795	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R796	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R801	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R802	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R803	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R804	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R805	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R806	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R807	QRE121J-101Y	C RESISTOR	100Ω 1/2W J
R809	NRSA63J-0R0X	MG RESISTOR	0Ω 1/16W J
R810	NRSA63J-391X	MG RESISTOR	390Ω 1/16W J
R811	NRSA63J-823X	MG RESISTOR	82kΩ 1/16W J
R812	NRSA63J-391X	MG RESISTOR	390Ω 1/16W J
R813	NRSA63J-823X	MG RESISTOR	82kΩ 1/16W J
R814	NRSA63J-104X	MG RESISTOR	100kΩ 1/16W J
R815	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R816	NRSA63J-750X	MG RESISTOR	75Ω 1/16W J
R818	NRSA63J-181X	MG RESISTOR	180Ω 1/16W J
R819	NRSA63J-221X	MG RESISTOR	220Ω 1/16W J
R820	NRSA63J-331X	MG RESISTOR	330Ω 1/16W J
R821	NRSA63J-471X	MG RESISTOR	470Ω 1/16W J
R822	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R823	QRE121J-470Y	C RESISTOR	47Ω 1/2W J
R824	NRSA63J-471X	MG RESISTOR	470Ω 1/16W J
R901	QRF154K-2R2	UNF WW RESISTOR	2.2Ω 15W K
R902	QRL029J-473	OMF RESISTOR	47kΩ 2W J
R903	QRL029J-333	OMF RESISTOR	33kΩ 2W J
⚠R910	QRZ0107-474Z	C RESISTOR	470kΩ 1/2W K
R921	QRE121J-101Y	C RESISTOR	100Ω 1/2W J
R922	QRZ0237-R18	UNF WW RESISTOR	0.18Ω 3W J
R923	QRT029J-R47	MF RESISTOR	0.47Ω 2W J
R924	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R929	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R930	QRL039J-473	OMF RESISTOR	47kΩ 3W J
⚠R932	QRZ9017-100	FUSI RESISTOR	10Ω 1/4W J
R934	QRE121J-102Y	C RESISTOR	1kΩ 1/2W J
R935	QRE121J-152Y	C RESISTOR	1.5kΩ 1/2W J
R951	QRE121J-102Y	C RESISTOR	1kΩ 1/2W J
R953	QRE121J-182Y	C RESISTOR	1.8kΩ 1/2W J
R962	QRL029J-223	OMF RESISTOR	22kΩ 2W J
R963	NRSA63J-223X	MG RESISTOR	22kΩ 1/16W J
R964	NRSA63J-473X	MG RESISTOR	47kΩ 1/16W J
R970	QRE121J-182Y	C RESISTOR	1.8kΩ 1/2W J
R973	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
R974	NRSA63J-102X	MG RESISTOR	1kΩ 1/16W J
R976	NRSA63J-391X	MG RESISTOR	390Ω 1/16W J
R977	QRL039J-120	OMF RESISTOR	12Ω 3W J
R978	NRSA63J-332X	MG RESISTOR	3.3kΩ 1/16W J
R981	NRSA63J-103X	MG RESISTOR	10kΩ 1/16W J
⚠R991	QRZ9046-825Z	C RESISTOR	8.2MΩ 1/2W K

⚠Ref No.	Part No.	Part Name	Description Local
L002	QQL244J-4R7Z	PEAKING COIL	4.7uH J
L003	QQL244J-4R7Z	PEAKING COIL	4.7uH J
L101	QQL244K-1R0Z	PEAKING COIL	1uH K
L351	QQL244J-220Z	COIL	22uH J
L522	QQR1005-004	LINEARITY COIL	
L551	QQLZ034-280	HEATER CHOKE	28uH
L651	QQL244J-4R7Z	PEAKING COIL	4.7uH J
L701	NQL092K-100X	COIL	10uH K
L702	NQL092K-100X	COIL	10uH K
L703	NQL092K-100X	COIL	10uH K
L704	NQL092K-100X	COIL	10uH K
L705	NQL092K-100X	COIL	10uH K
L706	NQL092K-100X	COIL	10uH K
L707	NQL092K-100X	COIL	10uH K
L708	NQL092K-100X	COIL	10uH K
L709	NQL092K-100X	COIL	10uH K
L710	NQL092K-100X	COIL	10uH K
L711	NQL092K-100X	COIL	10uH K
L712	NQL092K-100X	COIL	10uH K
L713	NQL092K-100X	COIL	10uH K
L714	NRSA02J-0R0X	MG RESISTOR	0Ω 1/10W J
L715	NQL092K-100X	COIL	10uH K
L716	NQL092K-100X	COIL	10uH K
L717	NQL092K-100X	COIL	10uH K
L951	QQLZ034-460	HEATER CHOKE	46uH
L952	QQL26AK-470Z	CHOKE COIL	47uH K
L954	QQL244J-5R6Z	COIL	5.6uH J
L972	QQL244J-5R6Z	COIL	5.6uH J
L973	QQL244J-5R6Z	COIL	5.6uH J
L975	QQL26AK-820Z	CHOKE COIL	82uH K
L994	NRSA02J-0R0X	MG RESISTOR	0Ω 1/10W J
T521	QQR1522-001	DRIVE TRANSF	
⚠T921	QQS0271-001	SW TRANSF	
⚠PC901	PS2581AL1/QW/	PHOTO COUPLER	
CF101	QAX0349-001	C TRAP	47.25MHz
⚠CP650	ICP-N50-Y	IC PROTECTOR	2.0A
⚠CP952	ICP-N38-Y	IC PROTECTOR	1.5A
⚠CP953	ICP-N38-Y	IC PROTECTOR	1.5A
⚠CP955	ICP-N75-Y	IC PROTECTOR	2.7A
⚠F901	QMF51E2-4R0J4	FUSE	4A AC250V
J801	QNZ0454-002	PIN JACK	VIDEO1/S-VIDEO
J802	QNN0349-002	PIN JACK	VIDEO2/COMP
J803	QNN0348-001	PIN JACK	VIDEO2/COMP
J804	QNN0349-001	PIN JACK	VIDEO OUT
J805	QNS0100-001	3.5 JACK	BASS SPEAKER OUT
J806	QNN0281-003	PIN JACK	VIDEO3(FRONT)/L3
J807	QNN0281-002	PIN JACK	VIDEO3(FRONT)/R3
J808	QNN0282-001	PIN JACK	VIDEO3(FRONT)/V3
J809	QNS0155-001	3.5 JACK	HEADPHONE
K101	QQR1114-001Z	FERRITE BEADS	
K103	QQR1114-001Z	FERRITE BEADS	
K107	QQR1114-001Z	FERRITE BEADS	
K108	QQR1114-001Z	FERRITE BEADS	
K355	QQR1113-001Z	FERRITE BEADS	
K901	QQR1114-001Z	FERRITE BEADS	
K921	QQR1114-001Z	FERRITE BEADS	
K922	QQR1114-001Z	FERRITE BEADS	
K951	QQR1114-001Z	FERRITE BEADS	
K952	QQR1113-001Z	FERRITE BEADS	
K953	QQR1113-001Z	FERRITE BEADS	
K955	QQR1113-001Z	FERRITE BEADS	
LC801	QQR1199-001	EMI FILTER	
LC802	QQR1199-001	EMI FILTER	
LC803	QQR1199-001	EMI FILTER	
LC804	QQR1199-001	EMI FILTER	
LC805	QQR1199-001	EMI FILTER	
⚠LF901	QQR0673-004	LINE FILTER	
⚠LF902	QQR1035-002	LINE FILTER	
⚠RY901	QSK0061-002	RELAY	
S801	QSW0619-003Z	TACT SWITCH	MENU
S802	QSW0619-003Z	TACT SWITCH	CH-
S803	QSW0619-003Z	TACT SWITCH	CH+
S804	QSW0619-003Z	TACT SWITCH	VOL-
S805	QSW0619-003Z	TACT SWITCH	VOL+
⚠S901	QSW0750-001	PUSH SWITCH	POWER
SF102	QAX0723-001	SAW FILTER	
⚠SK351	QNZ0536-001	CRT SOCKET	
⚠TH901	QAD0134-4R5	P THERMISTOR	4.5Ω
TU001	QAU0353-001	TUNER	
⚠VA901	QAF0060-621	VARISTOR	620V
X701	QAX0799-001Z	CRYSTAL	
	LC30114-001C-H	LED HOLDER	
	LC41232-001A-H	EE HOLDER	

Digitized in Heiloo Netherland

REMOTE CONTROL UNIT PARTS LIST (RM-C1282-2H)

⚠	Ref No.	Part No.	Part Name	Description	Local
		R25-8566	BATTERY COVER		

PACKING



PACKING PARTS LIST

⚠	Ref.No.	Part No.	Part Name	Description	Local
	1	GG10044-089A-H	PACKING CASE		
	2	GG10188-001C-H	CUSHION ASS'Y	4pcs in 1set	
	3	GG30097-003A-H	POLY BAG		
	4	GG30096-001A-H	POLY BAG		
	5	----------	BATTERY	AA/R6 (x2)	
⚠	6	GGT0040-001B-H	INST BOOK		
	7	CEAB004-001	MATCHING UNIT		
	8	CP30967-007-H	POLY BAG		AV-21VT34/P
	9	GG10142-001B-H	BASS TOP CUSHION		AV-21VT34/P
	10	RM-C1282-2H	REMOCON UNIT		
	11	GG20025-005A-H	CORNER LABEL	(x2)	AV-21VT14/P
	11	GG20070-002A-H	CORNER LABEL	(x2)	AV-21VT34/P

Digitized in Heiloo Netherland

www.freeservicemanuals.info

JVC

SCHEMATIC DIAGRAMS

FLAT COLOR TELEVISION

AV-21VT14/P,
AV-21VT34/P

CD-ROM No.SML200410

BASIC CHASSIS
CW



COPYRIGHT © 2004 Victor Company of Japan, Limited
Digitized in Heiloo Netherland

No.YA140
2004/10

www.freeservicemanuals.info

AV-21VT14/P, AV-21VT34/P

STANDARD CIRCUIT DIAGRAM

■ NOTE ON USING CIRCUIT DIAGRAMS

1.SAFETY

The components identified by the ⚠ symbol and shading are critical for safety. For continued safety replace safety ciritical components only with manufactures recommended parts.

2.SPECIFIED VOLTAGE AND WAVEFORM VALUES

The voltage and waveform values have been measured under the following conditions.

(1)Input signal	: Colour bar signal
(2)Setting positions of each knob/button and variable resistor	: Original setting position when shipped
(3)Internal resistance of tester	: DC 20kΩ/V
(4)Oscilloscope sweeping time	: H ⇒ 20μs / div
	: V ⇒ 5ms / div
	: Othters ⇒ Sweeping time is specified
(5)Voltage values	: All DC voltage values

∗ Since the voltage values of signal circuit vary to some extent according to adjustments, use them as reference values.

3.INDICATION OF PARTS SYMBOL [EXAMPLE]

● In the PW board : R209 → R209

4.INDICATIONS ON THE CIRCUIT DIAGRAM

(1)Resistors

● Resistance value

No unit	: [Ω]
K	: [kΩ]
M	: [MΩ]

● Rated allowable power

No indication	: 1/16 [W]
Others	: As specified

● Type

No indication	: Carbon resistor
OMR	: Oxide metal film resistor
MFR	: Metal film resistor
MPR	: Metal plate resistor
UNFR	: Uninflammable resistor
FR	: Fusible resistor

∗ Composition resistor 1/2 [W] is specified as 1/2S or Comp.

(2)Capacitors

● Capacitance value

1 or higher	: [pF]
less than 1	: [μF]

● Withstand voltage

No indication	: DC50[V]
Others	: DC withstand voltage [V]
AC indicated	: AC withstand voltage [V]

∗ Electrolytic Capacitors

47/50[Example]: Capacitance value [μF]/withstand voltage[V]

● Type

No indication	: Ceramic capacitor
MM	: Metalized mylar capacitor
PP	: Polypropylene capacitor
MPP	: Metalized polypropylene capacitor
MF	: Metalized film capacitor
TF	: Thin film capacitor
BP	: Bipolar electrolytic capacitor
TAN	: Tantalum capacitor

(3)Coils

No unit	: [μH]
Others	: As specified

(4)Power Supply

: B1

: B2 (12V)

: 9V

: 5V

∗ Respective voltage values are indicated

(5)Test point

: Test point

: Only test point display

(6)Connecting method

: Connector

: Wrapping or soldering


: Receptacle

(7)Ground symbol

: LIVE side ground

: ISOLATED(NEUTRAL) side ground

: EARTH ground

: DIGITAL ground

5.NOTE FOR REPAIRING SERVICE

This model's power circuit is partly different in the GND. The difference of the GND is shown by the LIVE : (⊥) side GND and the ISOLATED(NEUTRAL) : (⏚) side GND. Therefore, care must be taken for the following points.

(1)Do not touch the LIVE side GND or the LIVE side GND and the ISOLATED(NEUTRAL) side GND simultaneously. if the above caution is not respected, an electric shock may be caused. Therefore, make sure that the power cord is surely removed from the receptacle when, for example, the chassis is pulled out.

(2)Do not short between the LIVE side GND and ISOLATED(NEUTRAL) side GND or never measure with a measuring apparatus measure with a measuring apparatus (oscilloscope, etc.) the LIVE side GND and ISOLATED(NEUTRAL) side GND at the same time. If the above precaution is not respected, a fuse or any parts will be broken.

◆ **Since the circuit diagram is a standard one, the circuit and circuit constants may be subject to change for improvement without any notice.**

NOTE

◆ **Due improvement in performance, some part numbers show in the circuit diagram may not agree with those indicated in the part list.**
When ordering parts, please use the numbers that appear in the Parts List.

Digitized in Heiloo Netherland

CONTENTS

SEMICONDUCTOR SHAPES 2-2
USING P.W.BOARD 2-2
BLOCK DIAGRAM 2-3
CIRCUIT DIAGRAMS
MAIN PWB CIRCUIT DIAGRAM [AV-21VT14/P] (1/3) 2-5
MAIN PWB CIRCUIT DIAGRAM [AV-21VT14/P] (2/3),(3/3) 2-7
MAIN PWB CIRCUIT DIAGRAM [AV-21VT34/P] (1/3) 2-9
MAIN PWB CIRCUIT DIAGRAM [AV-21VT34/P] (2/3),(3/3) 2-11
PATTERN DIAGRAMS
MAIN PWB PATTERN 2-13
VOLTAGE CHART 2-15
WAVEFORMS 2-16

SEMICONDUCTOR SHAPES

TRANSISTOR

BOTTOM VIEW	FRONT VIEW				TOP VIEW
					CHIP TR 

IC

BOTTOM VIEW	FRONT VIEW			TOP VIEW
				

CHIP IC

TOP VIEW		
		

USING P.W. BOARD

P.W. BOARD ASS'Y NAME	AV-21VT14/P	AV-21VT34/P
MAIN P.W. BOARD	SCW-1039A-H2	SCW-1038A-H2

Digitized in Heiloo Netherland

www.freeservicemanuals.info

BLOCK DIAGRAM



Digitized in Helloo Netherland

www.freeservicemanuals.info

CIRCUIT DIAGRAMS

MAIN PWB CIRCUIT DIAGRAM [AV-21VT14/P] (1/3)



Digitized in Heifoo Netherland

www.freeservicemanuals.info

MAIN PWB CIRCUIT DIAGRAM [AV-21VT14/P] (2/3),(3/3)



NOTE

0 : NRSA63J-0R0X
*1 : 2SC3928A/QR/-X
*2 : 2SA1530A/QR/-X
*3 : MA111-X
*4 : MA3100/M/-X
*5 : UN2212-X
*6 : RGP10J-5025-T3
*7 : QQR1113-001Z
*8 : MA8091/H/-X
BW : QUY160-050Y
X : OPTION (OPEN)

DIFFERENCE PART LIST

	21VT14PA SCW-1039A	21VP14TA SCW-1065A	21WA14PA SCW-1055A
POWER CORD	QMY0360 ~165~K2	QMY0520 ~170~JC	QMY0362 ~165~K2

MAIN PWB ASS'Y (2/3)
SCW-1039A-H2 [AV-21VT14/P]

NOTE) 1.Refer to page 2-15 for voltages of this circuit diagram.
2.Refer to page 2-16 for waveforms of this circuit diagram.

Digitized in Heiloo Netherland

www.freeservicemanuals.info

MAIN PWB CIRCUIT DIAGRAM [AV-21VT34/P] (1/3)



Digitized in Heifoo Netherland

www.freeservicemanuals.info

MAIN PWB CIRCUIT DIAGRAM [AV-21VT34/P] (2/3),(3/3)



NOTE

0 : NRSA63J-0R0X
*1 : 2SC3928A/QR/-X
*2 : 2SA1530A/QR/-X
*3 : MA111-X
*4 : MA3100/M/-X
*5 : UN2212-X
*6 : RGP10J-5025-T3
*7 : QQR1113-001Z
*8 : MA8091/H/-X
BW : QUY160-050Y
X : OPTION (OPEN)

MAIN PWB ASS'Y (2/3)
SCW-1038A-H2 [AV-21VT34/P]

NOTE) 1.Refer to page 2-15 for voltages of this circuit diagram.
2.Refer to page 2-16 for waveforms of this circuit diagram.

Digitized in Heiloo Netherland

PATTERN DIAGRAMS

MAIN PWB PATTERN



Digitized in Heifoo Netherland

VOLTAGE CHARTS

<MAIN PWB>

PIN NO.	VOLTAGE(V)
IC401	
1	0.5
2	13.3
3	-11.9
4	-13.5
5	0.2
6	13.5
7	0.6
IC601	
1	0
2	0
3	23.5
4	0
5	0
6	0
7	11.7
8	2.1
9	0
10	24.8
11	15.8
12	11.7
IC701	
1	0
2	0
3	1.8
4	3.2
5	3.1
6	0.7
7	0
8	0.7
9	0
10	1.5
11	1.5
12	0
13	0.1
14	2.9
15	4.8
16	0.1
17	2.3
18	0
19	0.2
20	2.3
21	0.1
22	0.2
23	0.9
24	2.0
25	0.1
26	2.4
27	1.9
28	0
29	1.9
30	1.9
31	1.7
32	3.3
33	0.3
34	2.2
35	2.2
36	2.7
37	2.7
38	2.2
39	2.4
40	0
41	1.9
42	1.8
43	0.2
44	0.5
45	8.3
46	1.9
47	4.9
48	1.2
49	2.2
50	2.1
51	1.4
52	1.5
53	2.2
54	2.2
55	1.4
56	2.2
57	2.2
58	1.4
59	1.6
60	2.8
61	2.7
62	3.5
63	3.5
64	0.1
65	2.0
66	0.3
67	1.5
68	0
69	0.1
70	1.3
71	0.1
72	1.3
73	1.9

PIN NO.	VOLTAGE(V)
74	1.7
75	0.1
76	0
77	3.2
78	1.3
79	1.2
80	1.2
81	0
82	4.8
83	2.5
84	3.6
85	1.9
86	1.9
87	1.9
88	3.2
89	0
90	3.2
91	1.6
92	0
93	1.8
94	3.2
95	0
96	1.8
97	3.2
98	0.1
99	0.1
100	1.8
101	0
102	3.2
103	3.2
104	0
105	0
106	0
107	0
108	2.2
109	2.8
110	3.2
111	0
112	3.2
113	2.9
114	3.2
115	0
116	2.5
117	1.8
118	1.8
119	3.2
120	0
121	0
122	3.2
123	0
124	1.7
125	0
126	3.2
127	3.2
128	3.1
IC702	
1	0
2	0
3	0
4	0
5	3.1
6	3.1
7	0
8	3.2
IC801	
1	3.2
2	3.2
3	0
IC921	
1	302.6
3	0
4	19.8
5	0.1
6	1.3
7	0.7
IC951	
1	135.4
2	11.7
3	0
IC972	
1	7.2
2	0
3	3.3
IC973	
1	15.6
2	11.9
3	0
4	4.6

PIN NO.	VOLTAGE(V)
IC974	
1	1.8
2	0
3	0
4	0.5
5	2.8
6	0
7	3.2
IC975	
1	7.2
2	4.9
3	0
4	4.7
IC976	
1	1.8
2	0
3	0
4	0.5
5	2.9
6	0
7	3.2
Q101	
E	2.3
C	11.3
B	3.0
Q521	
E	0
C	11.0
B	0
Q522	
E	0
C	131
B	-0.1
Q571	
E	135.3
C	0
B	135.0
Q572	
E	0
C	3.2
B	0
Q601	
E	8.2
C	0.2
B	8.3
Q602	
E	0.2
C	-0.1
B	0
Q603	
E	0
C	0
B	-0.1
Q605	
E	0
C	0
B	-0.1
Q607	
E	0
C	0
B	0.7
Q608	
E	0
C	17.5
B	0
Q703	
E	3.2
C	0
B	3.2
Q705	
S	0
G	0.3
D	1.8
Q801	
E	1.9
C	0
B	1.2
Q803	
E	0
C	0
B	-0.4
Q804	
E	0
C	0
B	-0.3
Q805	
E	0.2
C	-0.4
B	0
Q955	
E	0
C	11.9
B	0

PIN NO.	VOLTAGE(V)
TU001	
1 (AGC)	1.8
2	3.5
3	0
4	2.3
5	2.3
6	4.9
7	4.8
8	0
9	34.3
10	-
11	0

<MAIN PWB (CRT SOCKET)>

PIN NO.	VOLTAGE(V)
IC351	
1	2.0
2	1.9
3	2.0
4	0
5	4.9
6	211.3
7	132.7
8	134.0
9	132.8

WAVEFORMS

-MAIN PWB-

IC401-1



0.6Vp-p

IC401-3



25Vp-p

IC401-5



55Vp-p

IC401-6



27Vp-p

IC401-7



0.6Vp-p

IC701-10



2.3Vp-p

IC701-11



3.1Vp-p

IC701-22

0.8Vp-p

IC701-23



1.1Vp-p

IC701-48



2.1Vp-p

IC701-66



5.4Vp-p

IC701-67



3.0Vp-p

IC701-74



1.2Vp-p

IC701-85



2.0Vp-p

IC701-86



1.6Vp-p

IC701-87



2.4Vp-p

T522-2



250Vp-p

T522-4



25Vp-p

T522-6



120Vp-p

T522-7



120Vp-p

T522-8



62Vp-p

T522-9



5.6Vp-p

Q521-B



2.7Vp-p

Q521-C



18Vp-p

Q522-B



2.3Vp-p

Q522-C



1050Vp-p

-CRT SOCKET PWB-

IC351-7



114Vp-p

IC351-8



142Vp-p

IC351-9



170Vp-p

Digitized in Heiloo Netherland

www.freeservicemanuals.info 7/23/2017

JVC

Victor Company of Japan, Limited
AV & MULTIMEDIA COMPANY VIDEO DISPLAY CATEGORY 12, 3-chome, Moriya-cho, kanagawa-ku, Yokohama, kanagawa-prefecture, 221-8528, Japan

(No.YA140)

Digitized in Heiloo Netherland

Printed in Japan
VPT